Date of issue: 01/07/09

Page 1 of 1



Sayerlack is a brand of The Sherwin-Williams Company SAYERLACK S.r.I. - Con Unico Socio Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18 tel. +39 051 770511 - fax +39 051 777437 www.sayerlack.it - www.lineabluvernici.it Cod. Fisc. e Reg. Impr. Bo 08866930152 - P. IVA: IT 00494251200 R.E.A. n. 313180 - Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531 Società soggetta a direzione e coordinamento di The Sherwin-Williams Company, USA



supersedes previous issue dated 21/06/04



WATERBORNE PIGMENTED METAL PASTE

Versions	XA0425/73	medium, aluminium	
	XA0426/34	coarse, gold	
	XA0426/73	coarse. aluminium	

Technical characteristics

Specific gravity (kg/l):	XA042*/XX	1.205 ± 0.030	
	XA0426/34	1.420 ± 0.030	
Solids content (%):	XA042*/XX	31 ± 1	
	XA0426/34	41 ± 1	

General characteristics

Shelf-life (months):

XA042*/XX is a range of metalized pastes suitable to obtain special effects and/or silver or golden coatings. The recommended dosage is 5-10% by weight, calculated on the clear matt binder for interiors used. The paste is to be mixed as long as required to obtain a perfect dispersion.

12

We recommend the use of XA042*/XX with waterborne topcoat, even pigmented.

General guidelines

Do not store at temperatures below 5°C. Stir well before use. Use spray guns equipped with a cup.

N.B.: Data provided on this Technical Data Sheet correspond to our best knowledge and experience. We assure consistency on the chemical-physical characteristics of our products, within the tolerance limits specified on our Technical Data Sheets. Responsibility of final result of product application is fully up to the users, who shall make sure that the product corresponds to their own needs with regard to application system, to substrates used as well as to working conditions.