

**PRODUCT NAME****Factory Floor Paint****HMG PAINTS LTD**

Collyhurst Road

Manchester, M40 7RU

Tel: 0161 205 7631 - Fax: 0161 205 8823

[www.hmgpaint.com](http://www.hmgpaint.com)[sales@hmgpaint.com](mailto:sales@hmgpaint.com)

**Issue date** 02/10/2003  
**Formula number**  
**Product code** TOPFLOOR  
**Printed date** Thu 11/08/05 at 14:39:37

**PACKAGING**

Available in standard pack sizes.

**PRODUCT FUNCTION**

HMG Factory Floor Paint has been designed to provide a hard wearing yet economical surface coating.

Its durability is achieved by the use of excellent quality resins, which also provide the user with a product that is very easy to use.

This product can be used by brush or roller as supplied or by Conventional/HVLP spray equipment with the addition of upto 20% HMG Thinner 2611.

**TECHNICAL INFORMATION**

Solids Approximately 35 to 55% dependent on colour  
 Flashpoint Above 32°C  
 Specific Gravity 0.98 to 1.30 approximately dependent on colour  
 Viscosity 3 poise ICI Cone And Plate  
 Storage 12 months in original sealed containers

**APPLICATION AND USAGE DATA**

Touch dry 2 - 4 hours  
 Hard dry 24 hours  
 Thinners Thinner 2612 or 2611  
 Overcoating 24 hours minimum  
 Eqp. cleaning GUNCLEANER 401  
 Environment Industrial  
 Film thickness 50 microns WFT gives approximately 25 microns DFT  
 Coverage 10 square metres per litre (theoretical)  
 VOC 420g/l approximately, fluorescents 650g/l

**COLOUR RANGE**

Grey &amp; Red Oxide.

**SPECIAL PROPERTIES**

- Resistance to diesel and oils at a competitive price.
- Easy to apply.
- Very good durability.

**PREPARATION**

Surfaces must be thoroughly clean, dry, sound and free of all contamination.

Concrete floors must be prepared thoroughly to ensure adequate adhesion.

**HOW TO USE**

- Airless       Brush       Electrostatic       HVLP  
 Conventional spray       Dipping       Roller       See application data

**APPLICATION**

HMG Factory Floor Paint can be used as supplied from the can or by Conventional/HVLP spray equipment with the addition of upto 20% Thinner 2611.

**HEALTH AND SAFETY**

- Refer to health & safety data sheet and tin label prior to use.
- Respiratory equipment should be worn when spraying.

**Technical Data Sheets are also available on our website at [www.hmgpaint.com](http://www.hmgpaint.com)**

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. Such information is to the best of HMG's knowledge and belief accurate and reliable as of the date indicated. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. For Professional Use Only.

Ref:541