

Technical Data Sheet



A thinner designed for dilution of 2 pack solvent based Epoxy paints to allow application by a variety of spray equipment.

| Physical parameters | |
|-------------------------|------------------------|
| Viscosity (Ford cup #4) | 12 – 18" |
| Specific gravity | 0,85 g/cc |
| Colour | Colourless |
| In-can appearance | Fluid liquid |
| Stability | 12 months at 10 – 25°C |

| Product use information | | | | | | | |
|-------------------------|---|--|--|--|--|--|--|
| Application process | Use as a thinner to mix with the base coating. Can also be used for | | | | | | |
| | equipment cleaning purposes. | | | | | | |
| Product preparation | Ensure thorough mixing prior to use | | | | | | |

| Safety Consult package labelling. All safety information related to this | in product |
|--|------------|
| | is product |
| can be found in the relevant product safety data sheet | |
| Storage 1 year | |



IRURENAGROUP

This technical data sheet aims to inform our customers about the properties of our product. Although the data contained here is based on our knowledge and technical reports carried out according to the mentioned standards, the suitability for purpose of use should be confirmed under customer practical conditions.

| Product | Product code | Brand | Author | Date | Version | Replaces | Page | Language |
|----------|--------------|--------|------------------------------|----------|---------|----------------------|------|----------|
| ORART725 | ORART725/5 | OROPAL | IKI COATINGS – IRURENA GROUP | 12.12.19 | 1 | Any previous version | 1/1 | EN |