

Sayerlack is a brand of SHERWIN-WILLIAMS

SAYERLACK S.r.I. - With a Single Shareholder

Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18 tel. +39 051 770511 - fax +39 051 777437 www.sayerlack.it - www.lineabluvernici.it

Cod. Fisc. e Reg. Impr. Bo 08866930152 - P. IVA: IT 00494251200 R.E.A. n. 313180 - Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531 *Company under the direction and coordination of The Sherwin-Williams Company, USA*

Technical Data Sheet

IF1022/34 GOLD PIGMENTED EFFECT

DATE 29/09/10

Colour:	34 gold
Area of use:	frames, accessories for furniture
Method of use:	by spray (with semi-closed gun)
Technical characteristics	
Solids content (%):	11 ± 2
Specific gravity (kg/l):	0.900 ± 0.030

General characteristics

Viscosity (DIN 4 at 20℃):

If the product is properly stored, shelf-life is unlimited. After long periods of storage, always check homogeneity and stir well before use to eliminate any possible sediment.

11" ± 1"

To enable denibbing, we suggest to thin IF1022/34 with DT0436/00 at 20%.

Substrate preparation

With polyurethane or polyester basecoat, followed by proper sanding.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.