

Woodcare Milk and renovation



Your timber windows and doors are treated with a high performance industrial coatings system developed by PPG Industrial Coatings. While this system offers very long term protection against harsh exterior weather it eventually requires renovation, just like any other material. PPG Woodcare Milk has been developed specially for the PPG Wood Finishes coating systems for optimum protection against weather effects and thus contributes towards extending the renovation intervals.



The Wood Finishes products of PPG Industrial Coatings are used in an industrial environment but are also easy to combine with the maintenance products of PPG Architectural Coatings.



To extend the period until renovation is required we advise the following:

1. Clean coated timber surfaces on the windows and doors on a regular basis with a neutral detergent and water. To be on the safe side, at least once a year refresh the surface by applying the Woodcare milk. Cleaned and refreshed surfaces reduce damage, caused by dirt, hailstorms, small scratches at the surface and mould and ensure the surface is water repellent for longer.
2. Ensure physical damage to the coating is minimised. Only when the surface becomes damaged does the protective envelope become breached allowing moisture ingress and sunlight damage.
3. Ensure any damages caused when installation is taking place are promptly repaired. This maintains the effectiveness of the protective envelope as described above.



WOOD FINISHES

How to use the Woodcare Milk

1. Clean wooden elements to be processed with PPG Woodcare Milk with a neutral detergent and water and wait until it fully dries.
2. Try applicability on an unobtrusive part of the wooden surface.
3. Apply some PPG Wood Care Milk on a soft wet lint-free cloth or moistened sponge.
4. Rub into the wood surface in accordance with the direction of growth rings to achieve a uniform coating. Avoid using the product in direct sunlight.
5. If PPG Wood Care Milk splashes onto items not to be coated wash these immediately with water. After drying the Wood Care Milk becomes transparent.

The Woodcare Milk:

- ✓ Restores gloss level helping improve water shedding properties of the coating system
- ✓ Provides a sacrificial coating that reduces the erosion of the factory applied coating system
- ✓ Regular use of the Woodcare Milk will provide extended intervals between renovation coatings.

For more information on PPG Wood Finishes visit www.ppgindustrialcoatings.com.



PPG Industrial Coatings

Bringing innovation to the surface.™

PPG Wood Finishes European local contact:

PPG Industrial Coatings BV; Postbus 920
3900 AX Veenendaal, NL; T 0318 567 800

PPG Polifarb Cieszyn S.A.; ul. Chemików 16
43-400 Cieszyn, PL; T +48 33 85 17 100

PPG Coatings Deutschland GmbH, An der Halde 1
44805 Bochum (D), Tel.: +49 3591 302688



©2012 PPG Industrial Coatings and
Bringing innovation to the surface are
registered trademarks of PPG Industries
Ohio, Inc.

www.ppgindustrialcoatings.com

industrial-coatings-emea@ppg.com

xx/14 IC003

