

PREDEC PRODUCTS WATER BASED including: Premium, Light, RSG and E544

PRODUCT DESCRIPTION

Translucent water based primers/basecoats based on acrylic dispersions.

AREAS OF USE

As primer/basecoats for internal and external joinery.

Predec RSG is particularly suited to sapelle and meranti timbers to provide colour harmonisation and sealing of endgrain.

PRODUCT CHARACTERISTICS

- Quick drying.
- Non-blocking.
- Excellent flexibility.
- Low odour.

METHODS OF APPLICATION AND USE OF PRODUCT

By dipping – the product is ready to use from the container, although the viscosity may be reduced by thinning with water to improve flow-off on complex shaped items of joinery.

Application conditions should be between 5°C and 40°C with a maximum relative humidity of 80%.

Stir contents of the container well before use.

Use tap water for thinning and the cleaning of equipment.

Consult Arch Coatings UK for advice before converting to water based from solvent based products.

DATA

Density (kg/lt):	around 1.1
Solids content (vol/vol):	20%-25%
Viscosity (DIN 4 at 20°C):	14-15 seconds
Drying times (20°C, 65% RH):	dust dry after 30 mins
	touch dry after 1 hour
	recoatible after 4 hrs
	stackable after 1½ hrs

Drying times are dependent on temperature and airflow and can be shortened with an increase in temperature or airflow.

STORAGE

Shelf life of one year in sealed unopened containers if stored between 5°C and 30°C under normal warehouse conditions. Protect from frost.

FURTHER INFORMATION

Read the separate Health and Safety sheet prior to use.

The data given above is average for various colours.

This is just one of a wide range of industrial wood coatings from Arch Coatings UK. Should you require any further information on this, or any other product within our range, simply contact us at the address below.