PREDEC SOLVENT BASED STAINS

PRODUCT DESCRIPTION

An alkyd based transparent pigmented basecoat.

AREAS OF USE

As a stain basecoat for internal and external joinery.

PRODUCT CHARACTERISTICS

- Excellent flexibility.
- Good durability.
- Provides up to 3 months on site protection prior to installation.

METHODS OF APPLICATION AND USE OF PRODUCT

By dipping – the product is ready to use from the container.

Applications conditions should be between 5ºC and 40ºC with a maximum relative humidity of 80%.

Stir contents of container well before use.

Use white spirit for the cleaning of equipment.

Consult Arch Coatings UK for advice prior to conversion from solvent based to this water based material.

DATA

Density:	1.1	
Solids content:	20	
Viscosity (DIN 4 @ 20ºC):	12-13 seconds	
Drying times:	handleable/touch dry	- after 2 hours
(20ºC, 65% RH)	stackable/recoatable	- after 10 hours

Drying times are dependent on temperature and can be shortened with an increase in temperature.

STORAGE

One year in sealed containers if stored between 5ºC and 30ºC under normal warehouse conditions. Protect from frost.

FURTHER INFORMATION

Read the separate Health and Safety sheet prior to use.

This is just one of a wide range of industrial wood coatings from Arch Coatings UK. Should you require any further information on this, or any other product within our range, simply contact us at the address below.