

TECHNICAL DATA SHEET

supersedes previous issue dated 26/11/2002

IF 1022/34

GOLD-O-LUX CAMPANIA

PRODUCT DESCRIPTION

Single pack metallic paint for picture frames and furniture accessories.

PRODUCT CHARACTERISTICS

A ready for use metallic product.

It is ideal for producing gilded picture frames and furniture components

MIXING PROCEDURE

If thinning is required use DT 450 thinners.

METHODS OF APPLICATION AND USE OF PRODUCT

Should be applied on well sanded NC or PU basecoats.

Application is by all spray types, the best results are obtained if the product is very well atomised and applied in light coats.

For extra durability over coating with PU or Acrylic topcoat is necessary. NC topcoats may cause discolouration of the gold powders.

DATA

Density:	0.900
Solids (w/w):	10
Viscosity (Ford 4 at 20°C):	11 secs
VOC g/lit	810
Thinning:	Use DT450 at up to 10%
Maximum number of coats:	1
Drying times:	Touch dry: 5-10 mins Over coating after 20 mins

STORAGE

Un limited shelf life, stir well before use.

FURTHER INFORMATION

Read the separate Health and Safety sheet prior to use.

This is just one of a wide range of industrial wood coatings from Arch. Should you require any further information on this, or any other product within our range, simply contact us at the address below.