

# sikkens

# Transparent

Factory Applied

## KODRIN WV470

# Coatings

**Transparent v-joint sealer for application to primed or base stained joinery.**

- Quick drying and recoat time
- Good adhesion to base stained or primed timber
- Easy to use
- Single pack
- Highly extensible
- Overcoatable with all Sikkens mid and top coat systems

**Composition**  
Polyacrylic resin.

**Drying Times**  
Recoat time is approximately 1 hour at 23°C and 50% relative humidity. The product must have become transparent before overcoating.

**Notes**  
Kodrin WV 470 must be recoated before being exposed externally.

**Flash Point**  
>100°C

**Method**  
Apply direct to V -joint from the cartridge with suitable nozzle. Level out with a spatula and ensure that product is not proud of the V -joint so that the product is not over applied. Do not apply when the temperature is below 10°C. Apply product over the base stain or primer.

**Cleaning**  
Clean equipment immediately after use with a solution of Sikkens ST830 and fresh luke warm water.

**Colour Range**  
Colourless only

**Pack Size**  
**320 ml cartridge**

**Storage**  
Store in a cool but frost free area.

**Recommended Recoating**  
Can be recoated with all Sikkens Joinery midcoat and top coat products.

## KODRIN WV470



## KODRIN WV470

It is our recommendation that all windows, doors, etc. should receive at least one coat of base stain or primer and one midcoat in the joinery factory prior to arrival on site. We would recommend you always seek exact system advice from our Customer Support Centre or one of our Joinery Account Managers.

Before using this product please read the Material Safety Data Sheet for Sikkens Kodrin WV 470. If you do not understand any part of this Technical Data Sheet, or the Material Safety Data Sheet, please contact the **Customer Support Centre** on **01480 496868**.

This data sheet supersedes all previous data sheets supplied relating to this product. It contains important information which must be communicated to the user. Users must satisfy themselves of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of Akzo Nobel Woodcare. Users must also satisfy themselves of the suitability of the product in circumstances other than those set out in this data sheet. Akzo Nobel Woodcare is always willing to answer user's enquiries regarding its products.

For further help and information on recommended coating systems and specifications please contact the **Customer Support Centre** on **01480 496868**.

The information above is correct at the date of issue 1/4/2002.

Product Code: 4ABXJ22700



**Akzo Nobel Woodcare**  
Meadow Lane, St Ives, Cambridgeshire PE27 4UY

Tel: 01480 496868 Fax: 01480 496801 E-mail: [sikkens@sis.akzonobel.com](mailto:sikkens@sis.akzonobel.com)  
[www.sikkens.co.uk](http://www.sikkens.co.uk)