

TECHNICAL DATA SHEET

supersedes previous issue dated 09/09/97

XP 566
WATER-REPELLENT WAX FOR FURNITURE

Area of use:	Panelling, furniture, garden chairs.
Method of use:	Brush, wiping, spray gun.
Thinning:	Ready to use.

Technical characteristics:

Solids content (%):	13 ± 1
Viscosity (DIN 2 at 20°C):	49" ± 5"
Specific gravity (kg/l):	0.796 ± 0.030
Drying time (100 g/m ² at 20°C):	Touch dry: 12 hours
Shelf-life:	If the product is properly stored, shelf-life is unlimited. After long periods of storage, always check homogeneity and stir well before use to eliminate any possible sediment.

General characteristics

This synthetic water-repellent wax is designed for treatment of veneer or solid wood parts requiring a natural, untreated look, but with a soft touch.

XP 566 can be applied by spray gun, brush or wiping. Once dry it forms a very thin layer, leaving the treated piece with a natural look but a very soft and smooth touch. The product also has very good water-repellency and good stain resistance. To increase the product's level of protection and smoothness, a second coat of XP 566 can be applied 24 hours after the first. XP 566 is not suitable for exterior exposure since it provides no protection against either blue staining fungi or degradation caused by UV radiation.

If thinning is required, use thinner DE 703.