



Flag French Polish

PRODUCT DATA

Description:

French polish for use on dark woods, or where light woods need to be slightly coloured. Can be mixed with transparent, or white polish, to provide a hint of colour.

Pour small quantities into a shallow receptacle and dip an applicator/brush. Apply with slow gentle pressure. Normally 3 coats are required, allow 24 hours between coats. Not recommended for outside use.

Area of use:

Interior

Substrates:

Wood

Physical Constants:

Colour:	Brown
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	18 sq. metres per litre
Flash point:	38°C
Specific gravity:	0.85
Dry to touch:	5 – 10 minutes (20°C)
Overcoating time:	15 – 20 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush, Cloth or Fad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Use a shellac sanding sealer to give a smooth surface prior to using brown french polish.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.