



MOVAC

PRODUCT TECHNICAL INFORMATION SHEET

PRODUCT CODE

MTW37** Range

DESCRIPTION

Water Based Graining Patine for dry removal.

AREAS OF USE

Graining Patine for Stain and Grain Door system.

PRODUCT CHARACTERISTICS

Easy removal characteristics giving uniform colour.
Supplied Ready for Use.
Available in a range of colours.

METHODS OF APPLICATION

Applied by spraygun on to a surface prepared with the relevant colour MTW25** Adhesion Promoter and allowed to dry to a uniform matt characteristic. The excess is then removed by scotchbrite pad, cloth or paper wiper.
Must be over coated with MTW45** Clear Lacquer before a period of 4-5 hours.
It is important to periodically agitate the product when in use as settlement may occur.

MIXING PROCEDURE

Supplied in a Ready For Use format (may be diluted up to a maximum of 5% with water if required).

DATA

Density (Kg/L)	1 to 1.4 Dependant on Colour
Solids Content (vol/vol)	33 to 45% Dependant on Colour
Drying Times @ 20°	
Dry to remove	4 – 10 minutes
Overcoatable	After excess removed.

STORAGE

Store above 5°C. Shelf life 12 months in sealed containers.

FURTHER INFORMATION

Read the separate health and safety sheet prior to use.

This is just one of a wide range of industrial coatings from Movac Group Ltd. Should you require any further information on this, or any other product within our range, simply contact us at the address below.