

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 1 of 12  
Print date: 27/01/2020

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours  
Product Code: 06R6190TR000MOV

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Dyeing and coloring of wood and other substrates

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **Industrias Químicas Irurena, S.A.**  
Address: Ctra. de Tolosa, s/nº. Apdo. 30  
City: 20730 Azpeitia  
Province: Gipuzkoa  
Telephone: 943 15 70 99  
Fax: 943 81 09 11  
E-mail: [irurena@irurenagroup.com](mailto:irurena@irurenagroup.com)  
Web: <http://www.irurenagroup.com>

**1.4 Emergency telephone number:** 915 620 420 (Inst.Toxicologia) (Available 24 hours)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:  
Flam. Liq. 3 : Flammable liquid and vapour.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

**Warning**

H statements:

H226 Flammable liquid and vapour.

P statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P370+P378 In case of fire: Use extinguisher powder or CO2 to extinguish.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container according to local regulations

#### 2.3 Other hazards.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 2 of 12  
Print date: 27/01/2020

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 607-025-00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01-2119485493-29-XXXX	[1] n-butyl acetate	2.5 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene (Mixture of isomers)	1 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	1 - 10 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

##### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

##### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

##### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

##### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 3 of 12  
Print date: 27/01/2020

### 4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

## SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

### 5.1 Extinguishing media.

#### Suitable extinguishing media:

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### 5.2 Special hazards arising from the mixture.

#### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 4 of 12  
Print date: 27/01/2020

### SECTION 7: HANDLING AND STORAGE.

#### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 1 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5.000	50.000

#### 7.3 Specific end use(s).

To be used within industrial facilities only

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

#### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
n-butyl acetate	123-86-4	United Kingdom [1]	Eight hours	150	724
			Short term	200	966
		United States [2] (Cal/OSHA)	Eight hours	150	
			Short term	200	
		United States [3] (NIOSH)	Eight hours	150	
			Short term	200	
xylene (Mixture of isomers)	1330-20-7	United States [4] (OSHA)	Eight hours	150	710
			Short term		
		European Union [5]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
		United Kingdom [1]	Eight hours	50	220
			Short term	100	441
		United States [2] (Cal/OSHA)	Eight hours	100	
			Short term	150 (Ceiling) 300	
		United States [3] (NIOSH)	Eight hours	100	
			Short term	150	
ethylbenzene	100-41-4	European	Eight hours	100	435
			Short term		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 5 of 12  
Print date: 27/01/2020

	Union [5]	Short term	200 (skin)	884 (skin)
	United Kingdom [1]	Eight hours	100	441
	United States [2] (Cal/OSHA)	Short term	125	552
	United States [3] (NIOSH)	Eight hours	5	
	United States [4] (OSHA)	Short term	30	
	United States [3] (NIOSH)	Eight hours	100	
	United States [4] (OSHA)	Short term	125	
	United States [4] (OSHA)	Eight hours	100	435
	United States [4] (OSHA)	Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[3] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[4] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	859,7 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	480 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	102,34 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	960 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	859,7 (mg/m <sup>3</sup> )
	DNEL (General population)	Oral, Long-term, Systemic effects	3,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	3,4 (mg/kg bw/day)
xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m <sup>3</sup> )
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m <sup>3</sup> )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
	aqua (intermittent releases)	0,36 (mg/l)
	STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg sediment dw)

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 6 of 12  
Print date: 27/01/2020




	sediment (marine water)	0,0981 (mg/kg sediment dw)
--	-------------------------	----------------------------------

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>	
<b>Uses:</b>	<b>Dyeing and coloring of wood and other substrates</b>	
<b>Breathing protection:</b>		
If the recommended technical measures are observed, no individual protection equipment is necessary.		
<b>Hand protection:</b>		
If the product is handled correctly, no individual protection equipment is necessary.		
<b>Eye protection:</b>		
PPE:	Face shield.	
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.	
CEN standards:	EN 165, EN 166, EN 167, EN 168	
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.	
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.	
<b>Skin protection:</b>		
PPE:	Anti-static protective clothing.	
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.	
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5	
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.	
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.	
PPE:	Anti-static safety footwear.	
Characteristics:	«CE» marking, category II.	
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346	
Maintenance:	The footwear should be checked regularly	
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.	

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour

Colour: N.A./N.A.

Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH: N.A./N.A.

Melting point: N.A./N.A.

Boiling Point: N.A./N.A.

Flash point: 39 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

**Version: 30**  
**Revision date: 27/01/2020**

**Page 7 of 12**  
**Print date: 27/01/2020**

Lower Explosive Limit: N.A./N.A.  
Upper Explosive Limit: N.A./N.A.  
Vapour pressure: N.A./N.A.  
Vapour density: N.A./N.A.  
Relative density: 1.240  
Solubility: N.A./N.A.  
Liposolubility: N.A./N.A.  
Hydrosolubility: N.A./N.A.  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: N.A./N.A.  
Decomposition temperature: N.A./N.A.  
Viscosity: N.A./N.A.  
Explosive properties: N.A./N.A.  
Oxidizing properties: N.A./N.A.  
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Pour point: N.A./N.A.  
Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.  
N.A./N.A. = Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 8 of 12  
Print date: 27/01/2020

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 11.037 mg/kg

b) skin corrosion/irritation;  
Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;  
Not conclusive data for classification.

d) respiratory or skin sensitisation;  
Not conclusive data for classification.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Not conclusive data for classification.

h) STOT-single exposure;  
Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;  
Based on available data, the classification criteria are not met.

j) aspiration hazard;  
Based on available data, the classification criteria are not met.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

There is no information available on the biodegradability of the substances present.

#### 12.2 Persistence and degradability.

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present. No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
n-butyl acetate N. CAS: 123-86-4      EC No: 204-658-1	1,78	-	-	Very low
ethylbenzene N. CAS: 100-41-4      EC No: 202-849-4	3,15	-	-	Moderate

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

**Version: 30**  
**Revision date: 27/01/2020**

**Page 9 of 12**  
**Print date: 27/01/2020**

### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13 DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.  
Follow the provisions of Directive 2008/98/EC regarding waste management.

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

### 14.1 UN number.

UN No: UN1263

### 14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT, 3, PG III, (D/E)

IMDG: UN 1263, PAINT, 3, PG III

ICAO/IATA: UN 1263, PAINT, 3, PG III

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

Labels: 3



Hazard number: 30  
ADR LQ: 5 L

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours

**OROPAL**  
INDUSTRIAL & DECORATIVE PAINTS SINCE 1923

Version: 30  
Revision date: 27/01/2020

Page 10 of 12  
Print date: 27/01/2020

IMDG LQ: 5 L  
ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E  
Proceed in accordance with point 6.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.**  
The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

VOC content (p/p): 25,362 %

VOC content: **314,491** g/l

##### USA:

VVOC content (p/p): 0 %

VVOC content: 0 g/l

VOC content (p/p): 25.362 %

VOC content: 314.491 g/l

SVOC content (p/p): .4 %

SVOC content: 4.96 g/l

VVOC: Very volatile organic compounds.

VOC: Volatile organic compounds.

SVOC: Semi volatile organic compounds.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5c

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
20. Organostannic compounds	<ol style="list-style-type: none"><li>1. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture is acting as biocide in free association paint.</li><li>2. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture acts as biocide to prevent the fouling by micro-organisms, plants or animals of:<ol style="list-style-type: none"><li>(a) all craft irrespective of their length intended for use in marine, coastal, estuarine and inland waterways and lakes;</li><li>(b) cages, floats, nets and any other appliances or equipment used for fish or shellfish farming;</li><li>(c) any totally or partly submerged appliance or equipment.</li></ol></li><li>3. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture is intended for use in the treatment of industrial waters.</li><li>4. Tri-substituted organostannic compounds:<ol style="list-style-type: none"><li>(a) Tri-substituted organostannic compounds such as tributyltin (TBT) compounds and triphenyltin (TPT) compounds shall not be used after 1 July 2010 in articles where the concentration in the article, or part thereof, is greater than the equivalent of 0,1 % by weight of tin.</li><li>(b) Articles not complying with point (a) shall not be placed on the market after 1 July 2010, except for articles that were already in use in the Community before that date.</li></ol></li><li>5. Dibutyltin (DBT) compounds:<ol style="list-style-type: none"><li>(a) Dibutyltin (DBT) compounds shall not be used after 1 January 2012 in mixtures and articles for supply to the general public where the concentration in the mixture or the article, or part thereof, is greater than the equivalent of</li></ol></li></ol>

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours



Version: 30  
Revision date: 27/01/2020

Page 11 of 12  
Print date: 27/01/2020

	<p>0,1 % by weight of tin.</p> <p>(b) Articles and mixtures not complying with point (a) shall not be placed on the market after 1 January 2012, except for articles that were already in use in the Community before that date.</p> <p>(c) By way of derogation, points (a) and (b) shall not apply until 1 January 2015 to the following articles and mixtures for supply to the general public:</p> <ul style="list-style-type: none"><li>- one-component and two-component room temperature vulcanisation sealants (RTV-1 and RTV-2 sealants) and adhesives,</li><li>- paints and coatings containing DBT compounds as catalysts when applied on articles,</li><li>- soft polyvinyl chloride (PVC) profiles whether by themselves or coextruded with hard PVC,</li><li>- fabrics coated with PVC containing DBT compounds as stabilisers when intended for outdoor applications,</li><li>- outdoor rainwater pipes, gutters and fittings, as well as covering material for roofing and façades,</li></ul> <p>(d) By way of derogation, points (a) and (b) shall not apply to materials and articles regulated under Regulation (EC) No 1935/2004.</p> <p>6. Dioctyltin (DOT) compound:</p> <p>(a) Dioctyltin (DOT) compounds shall not be used after 1 January 2012 in the following articles for supply to, or use by, the general public, where the concentration in the article, or part thereof, is greater than the equivalent of 0,1 % by weight of tin:</p> <ul style="list-style-type: none"><li>- textile articles intended to come into contact with the skin,</li><li>- gloves,</li><li>- footwear or part of footwear intended to come into contact with the skin,</li><li>- wall and floor coverings,</li><li>- childcare articles,</li><li>- female hygiene products,</li><li>- nappies,</li><li>- two-component room temperature vulcanisation moulding kits (RTV-2 moulding kits).</li></ul> <p>(b) Articles not complying with point (a) shall not be placed on the market after 1 January 2012, except for articles that were already in use in the Community before that date.</p>
--	---

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.(órganos de audición)

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4  
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4  
Asp. Tox. 1 : Aspiration toxicity, Category 1

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## 06R6190TR000MOV-Oropal 2k Direct to Metal Primer Finish Gloss Topcoat Colours



Version: 30  
Revision date: 27/01/2020

Page 12 of 12  
Print date: 27/01/2020

Flam. Liq. 2 : Flammable liquid, Category 2  
Flam. Liq. 3 : Flammable liquid, Category 3  
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3  
Skin Irrit. 2 : Skin irritant, Category 2

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
123-86-4	n-butyl acetate	Registered
1330-20-7	xylene (Mixture of isomers)	Registered
100-41-4	ethylbenzene	Registered

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.