

PRODUCT TECHNICAL INFORMATION SHEET

M136 (61776) PVC TOPCOATS

PRODUCT DESCRIPTION

Clear and pigmented solvent based lacquer and paint for PVC.

AREAS OF USE

For most types of flexible PVC

PRODUCT CHARACTERISTICS

Fast drying.
Very flexible.
Good opacity/hiding power.
Easy application.

METHODS OF APPLICATION AND USE OF PRODUCT

By brush and all spray types.
Ensure surface is clean and dry.

MIXING PROCEDURE

Ready for use.
Use Thinner 125 if required.

DATA

Solids (% w/w)	15-25 depending on colour.	
Density (kg/ltr)	0.95-1.15 depending on colour.	
Viscosity (Ford 4 @ 20°C)	51 Seconds	
Recommended film weight (g/m ²)	50-100	
Number of coats	2 max	
Drying times(80g/m ² @ 20°C)	dust free	10-15 mins.
	touch dry	20 mins
	Stackable	Overnight
Over coating	after 1 hour	

STORAGE

12 months in sealed containers

FURTHER INFORMATION

Read the separate Health and Safety sheet prior to use.

This is just one of a wide range of industrial coatings from Movac Group Limited
Should you require any further information on this, or any other product within our range, simply contact us at the address below.