Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS AF6020/00

SAFETY DATA SHEET

SECTION 1: Identifica	tion of the substance/mixture and of the company/undertaking
1.1 Product identifier	
Product name	: HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS
Product code	: AF6020/00
1.2 Relevant identified us	es of the substance or mixture and uses advised against
Material uses	: Paint or paint related material.
	Industrial use only.
1.3 Details of the supplier sheet	of the safety data
SHERWIN-WILLIAMS Ital	
Via del Fiffo, 12 - 40065 P	ianoro (BO)
Italia - C.P. 18 Cod. Fisc. e Reg. Impr. Bo	08866930152
e-mail address of persor	
responsible for this SDS	
1.4 Emergency telephone	number
National advisory body/	Poison Center
Telephone number	: 0844 892 0111
<u>Supplier</u>	
Telephone number	: +39 051 770511
Hours of operation	: Emergency contact available 24 hours a day
SECTION 2: Hazards	identification
2.1 Classification of the s	ubstance or mixture
Product definition	: Mixture
Classification according	to Regulation (EC) No. 1272/2008 [CLP/GHS]
The product is not classifie	ed as hazardous according to Regulation (EC) 1272/2008 as amended.
Classification according	to Directive 1999/45/EC [DPD]
The product is not classif	ied as dangerous according to Directive 1999/45/EC and its amendments.
Classification	: Not classified.
See Section 16 for the full	text of the R phrases or H statements declared above.
See Section 11 for more d	etailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.

Date of issue/Date of revision	: 18, Apr, 2015.
Dute of issue/Dute of revision	• 10, <i>T</i> (p), 2010.

SECTION 2: Hazards identification

Supplemental label elements

: Safety data sheet available on request.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Special packaging requirements Not applicable. Biocidal products regulation

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

:

3.2 Mixture

			Clas	sification	
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
1-Methyl-2-Pyrrolidone	REACH #: 01-2119472430-46	<5	Repr. Cat. 2; R61	Skin Irrit. 2, H315	[1] [2]
	EC: 212-828-1 CAS: 872-50-4 Index: 606-021-00-7		Xi; R36/37/38	Eye Irrit. 2, H319 Repr. 1B, H360D (Unborn child) STOT SE 3, H335	
				(Respiratory tract irritation)	
2-(2-Butoxyethoxy)- ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	>=1 - <5	Xi; R36	Eye Irrit. 2, H319	[1] [2]
Propylene Glycol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	>=1 - <5	Not classified.	Not classified.	[2]
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	 In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures		
5.1 Extinguishing media Suitable extinguishing media	: Recommended: alcohol-resistant foam, carbon dioxide, powders.	
Unsuitable extinguishing media	: Do not use water jet.	
5.2 Special hazards arising t	rom the substance or mixture	
Hazards from the substance or mixture	 Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. 	
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.	
Date of issue/Date of revision :	18, Apr, 2015. Date of previous issue : No previous validation. Version : 1 3/13	

HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS AF6020/00

SECTION 5: Firefighting measures

Special protective
equipment for fire-fighters: Fire-fighters should wear positive pressure self-contained breathing apparatus
(SCBA) and full turnout gear.

SECTION 6: Accidental release measures

Due to the organic solvents content of the mixture:

6.1 Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	xclude sources of ignition and ventilate the area. Avoid breathing vefer to protective measures listed in sections 7 and 8.	vapor or mist.
	eep unnecessary and unprotected personnel from entering.	
For emergency responders	specialised clothing is required to deal with the spillage, take note of a special of the spillage of the spil	
6.2 Environmental precautions	to not allow to enter drains or watercourses. If the product contami vers, or sewers, inform the appropriate authorities in accordance v egulations.	
6.3 Methods and materials for containment and cleaning up	contain and collect spillage with non-combustible, absorbent mater arth, vermiculite or diatomaceous earth and place in container for ccording to local regulations (see Section 13). Preferably clean wit void using solvents.	disposal
6.4 Reference to other sections	ee Section 1 for emergency contact information. ee Section 8 for information on appropriate personal protective eq ee Section 13 for additional waste treatment information.	uipment.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	: Due to the organic solvents content of the mixture:
handling	 Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Information on fire and explosion protection Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.
	ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any	: Store in accordance with local regulations. Notes on joint storage
incompatibilities	Keep away from: oxidizing agents, strong alkalis, strong acids. Additional information on storage conditions
	Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.
	Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
	Contaminated absorbent material may pose the same hazard as the spilled product. Store above $5^{\circ}C$ (42°F) Protect from frost.

Seveso II Directive - Reporting thresholds (in tonnes)

Name Notification and MAPP threshold Safety report threshold Formaldehyde concentration >= 90% 5 50

7.3 Specific end use(s) Recommendations : Not available. Industrial sector specific : Not available. solutions

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
1-Methyl-2-Pyrrolidone	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.
	STEL: 80 mg/m ³ 15 minutes.
	STEL: 20 ppm 15 minutes.
	TWA: 40 mg/m ³ 8 hours.
	TWA: 10 ppm 8 hours.
2-(2-Butoxyethoxy)-ethanol	EH40/2005 WELs (United Kingdom (UK), 12/2011).
	TWA: 10 ppm 8 hours.
	TWA: 67.5 mg/m ³ 8 hours.
	STEL: 15 ppm 15 minutes.
	STEL: 101.2 mg/m ³ 15 minutes.
Propylene Glycol	EH40/2005 WELs (United Kingdom (UK), 12/2011).
	TWA: 10 mg/m ³ 8 hours. Form: Particulate
	TWA: 474 mg/m ³ 8 hours. Form: Sum of vapour and particulates
	TWA: 150 ppm 8 hours. Form: Sum of vapour and particulates

HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS AF6020/00

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
	· Pequilar monitoring of all work areas should be carried out at all times including

: Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls		
Appropriate engineering controls	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn. Users are advised to consider national Occupational Exposure Limits or other	ors
	equivalent values.	
Individual protection meas	<u>S</u>	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, beforeating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothin Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Eye/face protection	Use safety eyewear designed to protect against splash of liquids.	
Skin protection		
Hand protection	Wear suitable gloves tested to EN374.	
Gloves	Short Term Exposure less than 10 minutes Continuous use Nitrile gloves.	
	Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time).	
	There is no one glove material or combination of materials that will give unlimited	
	resistance to any individual or combination of chemicals.	
	The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.	
	Gloves should be replaced regularly and if there is any sign of damage to the glove material.	Э
	Always ensure that gloves are free from defects and that they are stored and used correctly.	
	The performance or effectiveness of the glove may be reduced by physical/chemic damage and poor maintenance.	al
	Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.	е
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.	
Body protection	Personnel should wear protective clothing.	

SECTION 8: Exposure controls/personal protection

	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Recommended: A2P2 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Appearance	
Physical state	: Liquid.
Color	: Not available.
Odor	: Paint
Odor threshold	: Not Available (Not Tested).
рH	: 7.8
Melting point/freezing point	: Not Available (Not Tested).
Initial boiling point and boiling range	: 100°C
Flash point	: Closed cup: >93.3°C
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not Available (Not Tested).
Burning time	: Not Available (Not Tested).
Burning rate	: Not Available (Not Tested).
Upper/lower flammability or explosive limits	: Lower: 0.9% Upper: 12.5%
Vapor pressure	: 0.31 kPa [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 1.03
Solubility(ies)	: Not Available (Not Tested).
Solubility in water	: Not Available (Not Tested).
Partition coefficient: n-octanol/ water	: Not Available (Not Tested).
Auto-ignition temperature	: Not Available (Not Tested).
Decomposition temperature	: Not Available (Not Tested).
Viscosity	: Kinematic (room temperature): >0.07 cm ² /s Kinematic (40°C): >0.205 cm ² /s
Explosive properties	
Oxidizing properties	: Under normal conditions of storage and use, hazardous reactions will not occur.

9.2 Other information

SECTION 9: Physical and chemical properties

Heat of combustion	: 0.000003299 kJ/g				
SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.				
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.				
10.6 Hazardous decomposition products	 Under normal conditions of storage and use, hazardous decomposition products should not be produced. 				

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1-Methyl-2-Pyrrolidone	LD50 Dermal	Rabbit	8 g/kg	-
	LD50 Oral	Rat	3914 mg/kg	-
2-(2-Butoxyethoxy)-ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-

Acute toxicity estimates

Route	ATE value	
Dermal	32202.7 mg/kg	
Inhalation (vapors)	322 mg/l	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-Methyl-2-Pyrrolidone	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
2-(2-Butoxyethoxy)-ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-

HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS AF6020/00

SECTION 11: Toxicological information

Conclusion/Summary	: Not available.
<u>Sensitization</u> No data available	
Conclusion/Summary <u>Mutagenicity</u> No data available	: Not available.
Carcinogenicity	

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-Methyl-2-Pyrrolidone	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
No data available			
Aspiration hazard			
Product/ingredient name		Result	

No data available

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Product/ingredient name	Result	Species	Exposure
1-Methyl-2-Pyrrolidone	••	Daphnia - Daphnia magna Fish - Lepomis macrochirus	48 hours 96 hours
2-(2-Butoxyethoxy)-ethanol		Fish - Lepomis macrochirus	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.	•		•		
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
2-(2-Butoxyethoxy)-ethanol	-		-		Readily	

12.3 Bioaccumulative potential

Date of issue/Date of revision	: 18, Apr, 2015.	Date of previous issue	: No previous validation.	Version	:1	9/13
--------------------------------	------------------	------------------------	---------------------------	---------	----	------

HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS AF6020/00

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
No data available			

12.4 Mobility in soil Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.
12.5 Results of PBT and vP	B assessment
PBT	: Not applicable.
vPvB	: Not applicable.
12.6 Other adverse effects	: No known significant effects or critical hazards.
	 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13: Disposal considerations

13.1 Waste treatment metho	ds	
<u>Product</u>		
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:	No.
European waste catalogue (EWC)	:	08 01 12 waste paint and varnish other than those mentioned in 08 01 11
Disposal considerations	:	Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
<u>Packaging</u>		
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	:	Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	:	Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06.
Special precautions	:	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA		
14.1 UN number	Not regulated.	Not regulated.	Not regulated.		
14.2 UN proper shipping name	-	-	-		
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-		
14.4 Packing group	-	-	-		
14.5 Environmental hazards	No.	No.	No.		
Additional information	Special provisions Not Applicable	Emergency schedules (EmS) Not Applicable	Special provisions Not Applicable		

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in user the event of an accident or spillage.

: Not available. 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
1-Methyl-2-Pyrrolidone	Toxic to reproduction	Candidate	ED/31/2011	6/30/2011

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

SECTION 15: Regulatory information

Other EU regulations

European Directive	: EU limit value for this product (A/j): 140 g/L (2010). This product contains max VOC:
2004/42/EC	140 g/L

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
1-Methyl-2-Pyrrolidone	-	-	Repr. 1B, H360D (Unborn child)	-

Seveso II Directive

This product is controlled under the Seveso II Directive.

Name	
Formaldehyde (max.)	
National regulations	
Industrial use	The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
ternational regulations	
2 Chemical Safety sessment	 This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
Key literature references and sources for data	 Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road DPD = Dangerous Preparations Directive [1999/45/EC] DSD = Dangerous Substances Directive [67/548/EEC] IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 Directive 96/82/EC, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2000/39/EC, and relative amendments & additions CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

HYDRO WATERBORNE SELF-SEALER FOR PARQUET FLOORING - 20 GLOSS AF6020/00

SECTION 16: Other information		
Full text of abbreviated H statements	 H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. (Respiratory tract irritation) (Respiratory tract irritation) H360D May damage the unborn child. (Unborn child) 	
Full text of classifications [CLP/GHS]	 Eye Irrit. 2, H319 Repr. 1B, H360D (Unborn child) Skin Irrit. 2, H315 STOT SE 3, H335 (Respiratory tract irritation) SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 1 B SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 	
Full text of abbreviated R phrases	R61- May cause harm to the unborn child. R36- Irritating to eyes. R36/37/38- Irritating to eyes, respiratory system and skin.	
Full text of classifications [DSD/DPD]	 Repr. Cat. 2 - Toxic to reproduction category 2 Xi - Irritant 	
Date of printing	: 18, Apr, 2015.	
Date of issue/ Date of revision	: 18, Apr, 2015.	
Date of previous issue	: No previous validation.	
	: If there is no previous validation date please contact your supplier for more information.	
Version	: 1	

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.