

Technical Data Sheet

Diacetone Alcohol

DATE 02/07/12

Slow evaporating Stain thinners

Area of use:	For diluting XM8000 and XC1900 stains for spray wipe applications where large surfaces or high temperatures require slow evaporation of the media. Can be added to at <10% to water stains based on water diluted AC600 to improve the marking of the grain.
Method of use:	Use alone with Stain concentrates or add to DX986 to retard this thinner further.
VOC (g/l)	840

Technical Characteristics

Solids content (%):	0 ± 1
Specific gravity (kg/l):	0.840 ± 0.030
Viscosity seconds:	NA

Temperature for use	20°C
Shelf-life:	3 Years

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

Sayerlack is a brand of
SHERWIN-WILLIAMS

Sherwin-Williams UK Coatings Ltd

A1 Business Park - Knottingley - West Yorkshire - WF11 0BU - England
tel. +44 (0)1977 673363 - fax +44 (0)1977 673521
info@sayerlack.co.uk - www.sayerlack.co.uk
Technical Service: tel. +39 051 770770 - fax +39 051 770521
customerservice@sayerlack.it

Registered in England: 07148590
VAT REG No. GB 987 3607 68 - VAT REG No. IE 9741724H

General Characteristics

Special instructions

Do not use in water stains with XX4130 or waterbased lacquers have been used as a binder as this may cause the binder to coagulate.

Warning

Read the separate Health and Safety sheet prior to use. This is just one of a wide range of industrial wood coatings from Sherwin Williams. Should you require any further information on this, or any other product within our range, simply contact us at the address below.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.