

Technical Data Sheet

XA042*/XX WATERBORNE PIGMENTED METAL PASTE

Supersedes previous issue dated 21/06/04

DATE 01/07/09

Versions	XA0425/73	medium, aluminium
	XA0426/34	coarse, gold
	XA0426/73	coarse, aluminium

Technical characteristics

Specific gravity (kg/l):	XA042*/XX	1.205 ± 0.030
	XA0426/34	1.420 ± 0.030
Solids content (%):	XA042*/XX	31 ± 1
	XA0426/34	41 ± 1

General characteristics

Shelf-life (months):	12
----------------------	----

XA042*/XX is a range of metalized pastes suitable to obtain special effects and/or silver or golden coatings. The recommended dosage is 5-10% by weight, calculated on the clear matt binder for interiors used. The paste is to be mixed as long as required to obtain a perfect dispersion.

We recommend the use of XA042*/XX with waterborne topcoat, even pigmented.

General guidelines

Do not store at temperatures below 5°C.

Stir well before use.

Use spray guns equipped with a cup.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.