

Sayerlack is a brand of  
**SHERWIN-WILLIAMS**

**SAYERLACK S.r.l. - With a Single Shareholder**

Via del Fiffò, 12 - 40065 Pianoro (BO) - Italia - C.P. 18  
tel. +39 051 770511 - fax +39 051 777437  
www.sayerlack.it - www.lineablavernici.it

Cod. Fisc. e Reg. Impr. Bo 08866930152 - P. IVA: IT 00494251200

R.E.A. n. 313180 - Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

*Company under the direction and coordination of The Sherwin-Williams Company, USA*

## Technical Data Sheet

**XA4060/00**

**WASHING DETERGENT FOR WATERBORNE COATINGS**

*Supersedes previous issue dated 15/09/92*

*DATE 22/09/00*

### Technical characteristics:

Specific gravity (kg/l):	0.970 ± 0.030
Shelf-life (months):	15

### General characteristics

XA4060/00 is suitable for washing pumps, spray guns, nozzles and any other equipment used for application of waterborne coatings.

For best results equipment shall be washed with XA4060/00 immediately after use, then rinsed with water.

XA4060/00 is not a thinner. It is not recommended for cleaning automatic plants as it can remove and detach even dried films of waterborne coatings, which may end up clogging spray guns. It is advisable to let equipment soak in XA4060/00 for 1-2 hours, then rinse with water.

**N.B.:** DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

**WARNING:** ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.