



## Special Pale Polish

### PRODUCT DATA

---

#### Description:

A high quality polish made from the finest bleached dewaxed shellac. Most suitable for finishing items such as inlay and marquetry in view of its clarity of film.

#### Area of use:

Interior

#### Substrates:

Wood

#### Physical Constants:

Colour:	Transparent
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	18 sq. metres per litre
Flash point:	18°C
Specific gravity:	0.87 kg/litre
Dry to touch:	5 -10 minutes (20°C)
Overcoating time:	15 minutes

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### Application Details:

Application method:	Cloth and Fad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, dirt, grease and oil. Use a shellac sanding sealer prior to using Special Pale Polish

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.