

Technical Data Sheet

DSG 27

AC Thinners

Supersedes previous issue dated 02/05/07

DATE 22/03/12

Viscosity regulating thinners for Acid catalysed lacquers and paints. - General purpose thinner, Good drying range avoiding bubbles and defects.

Area of use:	For reducing the viscosity of lacquers and paints for application onto furniture.
Method of use:	All types of application
Mixing procedure:	Ready to Use

Technical Characteristics

Solids content (%):	0 ± 1
Specific gravity (kg/l):	0.880 ± 0.030
Viscosity seconds:	NA

Temperature for use	20°C
Shelf-life:	5 Years in sealed container

Warning

Read the separate Health and Safety sheet prior to use. This is just one of a wide range of industrial wood coatings from Sherwin Williams. Should you require any further information on this, or any other product within our range, simply contact us at the address below.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.