

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

- **1.1 Product identifier** For professional use only
- **Trade name:** **Hardener 9058 Standard**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture**
Surface Coating
Surface Coating
2K Epoxy Primer Hardener
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
HMG PAINTS LIMITED
RIVERSIDE WORKS, COLLYHURST ROAD,
MANCHESTER. M40 7RU
UNITED KINGDOM
TEL: +44 (0)161 205 7631
EMAIL: sales@hmgpaint.com
- **Further information obtainable from:** LABORATORY
- **1.4 Emergency telephone number:** +44 (0)161 205 7631 (Business hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Warning
- **Hazard statements**
Flammable liquid and vapour.
Causes skin irritation.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Specific treatment (see on this label).
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011

Trade name: Hardener 9058 Standard

(Contd. of page 1)

- **Additional information:**
Contains 3,6-diazaoctanethylenediamin. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7	Xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	50-100%
CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011

Trade name: Hardener 9058 Standard

(Contd. of page 2)

- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
- Keep receptacles tightly sealed.
- Ensure good ventilation/extraction at the workplace.
- Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 Xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.
- **Respiratory protection:** When spraying the product, use a respiratory protective device.
- **Protection of hands:**
- When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011

Trade name: Hardener 9058 Standard

(Contd. of page 3)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 137 °C

· **Flash point:** 25 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 500 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 7.0 Vol %

· **Vapour pressure at 20 °C:** 6.7 hPa

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with water:**

NOT MISCIBLE

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 62.5 %

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011

Trade name: **Hardener 9058 Standard**

(Contd. of page 4)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

1330-20-7 Xylene (mix)

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011


Trade name: **Hardener 9058 Standard**

(Contd. of page 5)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| · 14.1 UN-Number
· ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name
· ADR
· IMDG, IATA | 1263 PAINT (not viscous)
PAINT |
| · 14.3 Transport hazard class(es)
· ADR, IMDG, IATA | |
|  | |
| · Class
· Label | 3 Flammable liquids.
3 |
| · 14.4 Packing group
· ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards:
· Marine pollutant: | No |
| · 14.6 Special precautions for user
· Danger code (Kemler):
· EMS Number: | Warning: Flammable liquids.
30
F-E, <u>S-E</u> |
| · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR
· Limited quantities (LQ)
· Excepted quantities (EQ) | 5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| · Transport category
· Tunnel restriction code | 3
D/E |
| · IMDG
· Limited quantities (LQ)
· Excepted quantities (EQ) | 5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN1263, PAINT (not viscous), 3, III |

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Revision: 05.01.2011

Trade name: **Hardener 9058 Standard**

(Contd. of page 6)

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	62.5

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

· **Department issuing MSDS:** Product safety department: LABORATORY

· **Contact:** Health & Safety Officer

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3