390012400000-IRUFIRE FLOORING TOP COAT IFAT-1 AQUA DEEP MATT



Version 1Date of compilation: 3/01/2019Version 221 (replaces version 220)Revision date: 08/05/2022

Page 1 of 8 Print date: 08/05/2022

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:

IRUFIRE FLOORING TOP COAT IFAT-1 AQUA DEEP MATT

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Coating material for different surfaces

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	Industrías Químicas Irurena, S.A.
Address:	Ctra. de Tolosa, s/nº. Apdo. 30
City:	20730 - Azpeitia
Province:	Gipuzkoa
Telephone:	943 15 70 99
E-mail:	irurena@irurenagroup.com
Web:	https://www.irurenagroup.com

1.4 Emergency telephone number: 915 620 420 (Inst. Toxicologia) (Available 24 hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

The product is not classified as hazardous within the meaning of Regulation (EU) No 1272/2008.

2.2 Label elements.

Not classified as dangerous mixture according to EU 1272/2008

EUH statements: EUH210

UH210 Safety data sheet available on request.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification No 127	• • • •
Identifiers	Name	Concentrate	Classification	specific concentration limit

390012400000-IRUFIRE FLOORING TOP **COAT IFAT-1 AQUA DEEP MATT**



Date of compilation: 3/01/2019

Version 221 (replaces version 220) Revision date: 08/05/2022

Page 2 of 8 Print date: 08/05/2022

Index No: 603-096- 00-8 CAS No: 112-34-5 EC No: 203-961-6 Registration No: 01- 2119475104-44-XXXX	[1] 2-(2-butoxyethoxy)ethanol	1 - 10 %	Eye Irrit. 2, H319	-
(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.				

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

Inhalation.

Version 1

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eve contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing.

Ingestion.

Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account.

Fire protection equipment.

390012400000-IRUFIRE FLOORING TOP COAT IFAT-1 AQUA DEEP MATT

Version 1 Date of compilation: 3/01/2019

Version 221 (replaces version 220) Revision date: 08/05/2022

IRURENAGROUP Page 3 of 8 Print date: 08/05/2022

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended: For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures. As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 35 ° C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

••

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
	112-34-5	European	Eight hours	10	67,5
2 (2 hutova (athova () athonal		Union [1]	Short term	15	101,2
2-(2-butoxyethoxy)ethanol		United	Eight hours	10	67,5
		Kingdom [2]	Short term	15	101,2

390012400000-IRUFIRE FLOORING TOP COAT IFAT-1 AQUA DEEP MATT



Version 1 Date of compilation: 3/01/2019

Version 221 (replaces version 220) Revision date: 08/05/2022

Page 4 of 8 Print date: 08/05/2022

		Éire [3]	Eight hours	10	67,5
			Short term	12	101,2
[1] According both Binding Occupational	Esposure Limits	(BOELVs) and	d Indicative Occupatio	onal Exposure Limits	s (IOELVs) adopted

by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
2-(2-butoxyethoxy)ethanol CAS No: 112-34-5	DNEL (Workers)	Inhalation, Long-term, Local effects	67,5 (mg/m ³)
EC No: 203-961-6	DNEL (Workers)	Inhalation, Long-term, Systemic effects	67,5 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Concentration:	100 %
Uses:	Coating material for different surfaces
Breathing protec	tion:
If the recommende	d technical measures are observed, no individual protection equipment is necessary.
Hand protection:	
If the product is ha	ndled correctly, no individual protection equipment is necessary.
Eye protection:	
If the product is ha	ndled correctly, no individual protection equipment is necessary.
Skin protection:	
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it	
Maintenance.	not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any
	injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance:Liquid with characteristic odour and colour Colour: FALTA Odour:Poor Odour threshold:N.A./N.A. pH:7 (100%) Melting point: < 0 °C Boiling Point: 100 °C Flash point: 100 °C Flash point: 100 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): Non inflammable Lower Explosive Limit: Does not form explosive mixtures Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:More than air

390012400000-IRUFIRE FLOORING TOP COAT IFAT-1 AQUA DEEP MATT



Version 1Date of compilation: 3/01/2019Version 221 (replaces version 220)Revision date: 08/05/2022

Page 5 of 8 Print date: 08/05/2022

Relative density:1.030 Solubility:In water Liposolubility: No Miscible Hydrosolubility: Miscible Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: > 350°C Decomposition temperature: N.A./N.A. Viscosity: See Technical Data Sheet Explosive properties: Not Explosive Oxidizing properties: Non-Oxidizing

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A. Blink: N.A./N.A. Kinematic viscosity: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation; Not conclusive data for classification.

c) serious eye damage/irritation; Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

390012400000-IRUFIRE FLOORING TOP COAT IFAT-1 AQUA DEEP MATT

Version 1 Date of compilation: 3/01/2019 Version 221 (replaces version 220) Revision date: 08/05/2022

IRURENAGROUP Page 6 of 8 Print date: 08/05/2022

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
Name	Log Pow	BCF	NOECs	Level
2-(2-butoxyethoxy)ethanol	0,56	_	_	Verv low
CAS No: 112-34-5 EC No: 203-961-6	0,50		_	very low

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

390012400000-IRUFIRE FLOORING TOP **COAT IFAT-1 AQUA DEEP MATT**



Version 1 Date of compilation: 3/01/2019 Version 221 (replaces version 220) Revision date: 08/05/2022

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport. ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): j - Two-pack reactive performance coatings for specific end use such as floors, water-borne Phase I* (from 01/01/2007): 140 g/l Phase II* (from 01/01/2010): 140 g/l

(*) g/l ready to use

VOC content (p/p): 5,607 % VOC content: 95 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

390012400000-IRUFIRE FLOORING TOP **COAT IFAT-1 AQUA DEEP MATT**



Date of compilation: 3/01/2019 Version 1 Version 221 (replaces version 220) Revision date: 08/05/2022

Page 8 of 8 Print date: 08/05/2022

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H319 Causes serious eye irritation.

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is recommended that the product only be employed for the purposes advised.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
112-34-5	2-(2-butoxyethoxy)ethanol	Registered

Abbreviations and acronyms used:

BCF:	Bioconcentration	factor.

CEN: European Committee for Standardization.

- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.

NOEC: No observed effect concentration.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.