

COMPANY WITH MANAGEMENT SYSTEM - UNI EN ISO 9001 -- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18 tel. +39 051 770 511 - fax +39 051 777 437 www.sayerlack.com Cod. Fisc. e Reg. Impr. Bo 08866930152 P. IVA: IT 00494251200 - R.E.A. n. 313180 Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

Technical Data Sheet

CATALYST FOR ACID CURING SYSTEMS

Supersedes previous issue dated 07.05.12

DATE 07/01/16

Technical characteristics

CODE	SPECIFIC GRAVITY
WH0750/00	0.900 ± 0.030
WH0751/00	0.860 ± 0.030
WH1084/00	0.900 ± 0.030
WHL3593/00	0.960 ± 0.030

General characteristics

Shelf-life (months):

After long periods of storage, always check that the product is clear.

As to other characteristics and method of use, please refer to the technical data sheets relating to part A.

Be careful when using the product due to its acid nature. Wear protective gloves and goggles during use. Read and follow instructions contained in the safety data sheet.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.