

Technical Data Sheet

AP1104/XX
WATERBORNE ANTIQUE STAIN FOR DENIBBING
Supersedes previous issue dated 26/08/97

DATE 12/04/00

Colours available:	07 golden yellow	08 red	13 white
	14 dark blue	22 black	48 brown
	52 yellow iron oxide		
Area of use:	Picture frames, furniture, kitchen doors, turned parts, flat parts.		

Technical characteristics

Specific gravity (kg/l):	1.000 ÷ 1.400	depending on the colour
Solids content (%):	44 - 59	depending on the colour
Light fastness:	Good for interiors	
Shelf-life (months):	12	

General characteristics

The product can be thinned with water to a maximum of 50% and can be applied with fixed or manual spray guns on nitrocellulose, polyurethane or polyester basecoats.

After drying (30' at room temperature or 15' in hot air oven) it can be removed by rubbing with steel wool or scotch brite.

The antique stain must be fixed and protected with a clear top coat 4-5 hours after application.

Special instructions

Sediment may form in the bottom of the can, but can easily be dispersed by stirring with a stick.

Do not store at temperatures below 15°C.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.