

GET FRIENDLY WITH

 **SAYERLACK**[®]
INNOVATIVE WOOD SOLUTIONS

Oil Systems for Wood

OL Series

movac group
limited
the solution provider 

Hard wearing
Specially formulated
Easy & quick application

Oil Systems for Wood OL Series

OL3000/00 Hard oil for parquet application

OL3000/00 is an urethane oil especially developed for parquet application. We suggest to apply at least 2 coats of oil to obtain better chemical and mechanical resistance.

OL3100/00 Natural effect oil

OL3100/00 is a blend of special oils and selected waxes developed for easy and quick application. It enables waterproofing and preservation of wooden items while maintaining the original natural-wood appearance.

OL3300/00 Teak effect oil

OL3300/00 is a blend of natural oils developed for easy and quick maintenance of uncoated wooden items for exterior use such as flooring, swimming pools borders, public benches, garden furniture, etc. Thanks to its formulation it provides good protection against water.

OL3400/00 Wax effect oil

OL3400/00 can be applied using a spray gun, brush or cloth. We suggest applying at least 2 coats of oil to obtain better chemical and mechanical resistance. To achieve the best grain wetting we suggest diluting the first coat with 10%-30% (depending on the application) using a thinner such as DE0703/00.

OLV2322/00 Natural 'food contact' oil

OLV2322/00 is a natural oil suitable for the impregnation of wooden items for interior, intended to come into contact with foodstuffs. Non-toxic and odourless, this easy to use product can be applied by spray, brush or rag and has good waterproofness. This oil conforms to Ikea regulation IOS-RPG-0021, as certified by SGS institute.

After applying the oil we suggest removing the excess product using a cloth or paper wipe. It is not always required to brush the last layer of oil to achieve better resistance. Please remember to always soak the rags or paper wipes in water before disposing of them. This should prevent the oil residues setting fire to the used cloths or paper wipers!

KNOWLEDGE FRIENDLY

We have worldwide resources and commitment to R & D to ensure our products are the most advanced



Movac Group Limited Head Office: 11 Portman Road, Ipswich, Suffolk UK IP1 2BP
T 0844 561 0070 F 0844 561 0080 E info@movac.com www.movac.com

Cambridge:

T 01763 268487 F 01763 262369
E cambridge.depot@movac.com

Coventry:

T 02476 456454 F 02476 636946
E coventry.depot@movac.com

Ipswich:

T 01473 343999 F 01473 286225
E ipswich.depot@movac.com

Norwich:

T 01603 787474 F 01603 787434
E norwich.depot@movac.com

Nottingham:

T 0115 977 0108 F 0115 976 4534
E nottingham.depot@movac.com

Peterborough:

T 01733 558906 F 01733 358611
E peterborough.depot@movac.com

Reading:

T 0118 977 1198 F 0118 989 3516
E reading.depot@movac.com

Romford:

T 01708 374227 F 01708 386877
E romford.depot@movac.com

Vernici:

T 01603 894019 F 01603 787434
E sales@vernici.co.uk