

Technical Data Sheet

DT0040/00 SPECIAL THINNER FOR POLYURETHANE COATINGS

Supersedes previous issue dated 09/09/97

DATE 16/10/00

Technical characteristics

Specific gravity (kg/l):	0.882 ± 0.030
Flash-point (°C):	+23
Drying speed (max 100; min 0):	50
Resistivity (Mohm/cm at 20°C):	700
Shelf-life (months):	If the product is properly stored, shelf-life is unlimited.

General characteristics

DT0040/00 is a thinner for polyurethane coatings exhibiting medium-slow drying speed, which ensures excellent drying of the products thinned and improves their final appearance after drying.

Dosage: 20-50%

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.