

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** For professional use only
- **Trade name:** HB05 Grey Primer
- **Article number:** 10580
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture** Surface Coating
- **Uses advised against** Product is not intended, labelled or packaged for consumer use.
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
HMG PAINTS LIMITED
RIVERSIDE WORKS, COLLYHURST ROAD,
MANCHESTER. M40 7RU
UNITED KINGDOM
TEL: +44 (0)161 205 7631
EMAIL: sales@hmgpaint.com
- **Further information obtainable from:** sales@hmgpaint.com
- **1.4 Emergency telephone number:** +44 (0)161 205 7631 (Business hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Xylene (mix)
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: **HB05 Grey Primer**

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains 2-butanone oxime. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|---|--|---------|
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx | Xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 10-25% |
| EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx | Solvent naphtha (petroleum), light aromatic ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336 | 2.5-10% |
| CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-0000 | trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 2.5-10% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332 | ≤2.5% |
| CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28 | 2-butanone oxime ⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317 | ≤2.5% |

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

• **General information:** Immediately remove any clothing soiled by the product.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: **HB05 Grey Primer**

(Contd. of page 2)

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be [stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.] or [laid out flat in a single layer to dry] or [placed in a metal container soaked with water] or [washed out well with warm soapy water before disposal.] Contaminated materials should be removed from the workplace at the end of each working day and stored outside.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 3)

- **Further information about storage conditions:**
Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 Xylene (mix)

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
|-----|--|

Solvent naphtha (petroleum), light aromatic

| | |
|-----|--|
| OEL | Long-term value: 100 mg/m ³ |
|-----|--|

100-41-4 ethylbenzene

| | |
|-----|---|
| WEL | Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk |
|-----|---|

96-29-7 2-butanone oxime

| | |
|-----|--|
| OEL | Long-term value: 1 mg/m ³ , 0.3 ppm |
|-----|--|

- **DNELs**

1330-20-7 Xylene (mix)

| | | |
|------------|------|------------------------------|
| Dermal | DNEL | 108 mg/day (Con) |
| | | 180 mg/day (Ind) |
| Inhalative | DNEL | 14.8 mg/m ³ (Con) |
| | | 77 mg/m ³ (Ind) |

Solvent naphtha (petroleum), light aromatic

| | | |
|------------|------|-----------------------------|
| Oral | DNEL | 11 mg/day (Con) |
| Dermal | DNEL | 11 mg/day (Con) |
| | | 25 mg/day (Ind) |
| Inhalative | DNEL | 32 mg/m ³ (Con) |
| | | 150 mg/m ³ (Ind) |

7779-90-0 trizinc bis(orthophosphate)

| | | |
|------------|------|-----------------------------|
| Oral | DNEL | 0.83 mg/day (Con) |
| Dermal | DNEL | 83 mg/day (Con) |
| | | 83 mg/day (Ind) |
| Inhalative | DNEL | 2.5 mg/m ³ (Con) |
| | | 5 mg/m ³ (Ind) |

96-29-7 2-butanone oxime

| | | |
|------------|------|-----------------------------|
| Dermal | DNEL | 0.78 mg/day (Con) |
| Inhalative | DNEL | 1.3 mg/day (Ind) |
| | | 2.7 mg/m ³ (Con) |
| | | 9 mg/m ³ (Ind) |

- **PNECs**

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 4)

- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

| | |
|--|---------------------------------|
| · Ingredients with biological limit values: | |
| 1330-20-7 Xylene (mix) | |
| BMGV | 650 mmol/mol creatinine |
| | Medium: urine |
| | Sampling time: post shift |
| | Parameter: methyl hippuric acid |

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:** When spraying the product, use a respiratory protective device.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

- | | |
|---------------------------|-----------------|
| Form: | Liquid |
| Colour: | Grey |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

- | | |
|---|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 136 °C |

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 5)

| | |
|--|---|
| · Flash point: | 24 °C |
| · Flammability (solid, gas): | Not applicable. |
| · Ignition temperature: | 500 °C |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7 Vol % |
| · Vapour pressure at 20 °C: | 6.7 hPa |
| · Density at 20 °C: | 1.507 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with water: | NOT MISCIBLE |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic at 20 °C: | 220 mPas |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 25.4 % |
| Solids content: | 74.1 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

1330-20-7 Xylene (mix)

| | | |
|------------|----------|-------------------|
| Oral | LD50 | 5,000 mg/kg (Rat) |
| Dermal | LD50 | 2,000 mg/kg (rbt) |
| Inhalative | LC50/4 h | 11 mg/l (Rat) |

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 6)

| Solvent naphtha (petroleum), light aromatic | | |
|--|----------|--|
| Oral | LD50 | 3,492 mg/kg (rat) |
| Dermal | LD50 | 3,160 mg/kg (Rab) |
| Inhalative | LC50/4 h | 6,193 mg/l (rat) |
| 7779-90-0 trizinc bis(orthophosphate) | | |
| Oral | LD50 | >5,000 mg/kg (rat) |
| Inhalative | LC50/4 h | >5.7 mg/l (Rat) |
| 100-41-4 ethylbenzene | | |
| Oral | LD50 | 3,500 mg/kg (rat) |
| Dermal | LD50 | 17,800 mg/kg (rbt) |
| 96-29-7 2-butanone oxime | | |
| Oral | LD50 | 2,326 mg/kg (rat) |
| Dermal | LD50 | 1,000 mg/kg (Rab) 200-2,000 mg/kg (rat) |
| Inhalative | LC50/4 h | >4.8 mg/l (rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
- Acute Fish toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
LC50 9.22 mg/l
Species: *Oncorhynchus mykiss* (rainbow trout)
Exposure duration: 96 h
- Acute toxicity for daphnia
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
EC50 6.14 mg/l
Species: *Daphnia magna* (Water flea)
Exposure duration: 48 h
- Acute toxicity for algae
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
ErC50 2.9 mg/l
Species: *Pseudokirchneriella subcapitata* (green algae)
Exposure duration: 72 h
- Acute bacterial toxicity
Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)
EC50 1 - 10 mg/l

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 7)

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %)

Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**· **ADR**· **IMDG**· **IATA**1263 PAINT, ENVIRONMENTALLY HAZARDOUS
PAINT (Solvent naphtha (petroleum), light aromatic,
trizinc bis(orthophosphate)), MARINE POLLUTANT
PAINT· **14.3 Transport hazard class(es)**· **ADR, IMDG**· **Class**· **Label**

3 Flammable liquids.

3

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 8)

· IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group III
· ADR, IMDG, IATA

· 14.5 Environmental hazards: Product contains environmentally hazardous substances: trizinc bis(orthophosphate)
· Marine pollutant: Symbol (fish and tree)
· Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Flammable liquids.
· Danger code (Kemler): 30
· EMS Number: F-E, S-E
· Stowage Category A

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
· Transport category 3
· Tunnel restriction code D/E

· IMDG
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: HB05 Grey Primer

(Contd. of page 9)

· **National regulations:**· **Technical instructions (air):**

| Class | Share in % |
|-------|------------|
| I | 0.3 |
| NK | 25.4 |

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Full text of H-Statements referred to under sections 2 and 3:**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department: LABORATORY· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2