(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 1 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: HIDRON SP-146 White Product Code: 920014600000

1.2 Relevant identified uses of the mixture and uses advised against.

Coating material for different surfaces

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: Industrías Químicas Irurena, S.A.

Address: Ctra. de Tolosa, s/nº. Apdo. 30

City: 20730 Azpeitia
Province: Gipuzkoa
Telephone: 943 15 70 99
Fax: 943 81 09 11
E-mail: sds@irurena.com

Web: http://www.irurenagroup.com

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

The product is not classified as hazardous within the meaning of Regulation (EU) No 1272/2008.

2.2 Label elements.

EUH statements:

EUH208 Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1),mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 2 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

Index No: 603-014- 00-0 CAS No: 111-76-2 EC No: 203-905-0 Registration No: 01- 2119475108-36-XXXX	[1] 2-butoxyethanol,	>=1% < 2,5%	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
--	----------------------	-------------	--	---

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

^{*} See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

^[1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 3 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended:

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures.

As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 35° C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

..

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
		European	Eight hours	20 (skin)	98 (skin)
2-butoxyethanol,	111-76-2	Union [1]	Short term	50 (skin)	246 (skin)
		United	Eight hours	25	123
		Kinadom [2]	Short term	50	246

[1] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
2-butoxyethanol,	DNEL	Inhalation, Long-term, Systemic effects	98
N. CAS: 111-76-2	(Workers)		(mg/m³)
N. CE: 203-905-0			

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 4 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Breathing protection: If the recommended technical measures are observed, no individual protection equipment is necessary. Hand protection: PPE: Work gloves. CEN standards: CEN marking, category I. EN 374-1, EN 374-2, EN 374-3, EN 420 Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Breakthrough time Standards: PVC (polyvinyl chloride) Breakthrough time Material thickness (mm): Eye protection: PPE: Face shield. Face shie	Concentration:	100 %			
If the recommended technical measures are observed, no individual protection equipment is necessary. Hand protection: PPE:		Coating material for different surfaces			
Hand protection: PPE:	Breathing protection:				
PPE: Characteristics:	If the recommended technical measures are observed, no individual protection equipment is necessary.				
Characteristics: CEN standards: CEN standard	Hand protection:				
EN 374-1, En 374-2, EN 374-3, EN 320 Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) PVC (polyvinyl chloride) Face shield. Characteristics: CEN standards: EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Sakin protection: PPE: Characteristics: CEN standards: Maintenance: Protective clothing. ACE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Characteristics: CEN standards: Naintenance: Work footwear. CEN marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.					
Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Observations: Material: PVC (polyvinyl chloride) PVC (polyvinyl chloride) Face shield. Characteristics: CEN standards: Discription: PE: Characteristics: CEN standards: Skin protection: PPE: Characteristics: CEN standards: Characteristics: CEN standards: Discription: POE: Characteristics: CEN standards: Characteristics: CEN standards: Discription: POE: Characteristics: CEN standards: Characteristics: CEN standards: CEN standards: Discription: POE: Characteristics: CEN standards: Maintenance: Discription: POE: Characteristics: CEN standards: CEN standards: Maintenance: Maintenance: Work footwear. Characteristics: CEN standards: CEN standards: Discription: POE: Work footwear. CEN standards: CEN standar	Characteristics:				
Maintenance: Observations: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) PE: Characteristics: CEN standards: Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Breakthrough time	CEN standards:				
adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands. Material: PVC (polyvinyl chloride) PE: Characteristics: CEN standards: CEN standards: Characteristics: CEN standards: CEN	Maintonanco				
Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time (min.): A80 Material thickness (nmm): 0,35 Eye protection: PPE: Face shield. Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Pace shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Skin protection: PPE: Protective clothing. CCE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. CE» marking, category II. ET SD 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Maintenance.				
Always use with clean, dry hands. Material: PVC (polyvinyl chloride) Breakthrough time (min.): A80 Material thickness (nmm): 0,35 Eye protection: PPE: Face shield. Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Pace shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Skin protection: PPE: Protective clothing. CCE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements. EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. CE» marking, category II. ET SD 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	01				
Five (polyyliny Chloride) (min.): Five (polyyliny Chloride) (min.): Five protection: Face shield. (Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid. (Characteristics: EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.	Observations:				
PPE: Characteristics: CEN standards: EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Observations: PRE: Characteristics: CEN standards: Maintenance: Maintenance: Description: PPE: Characteristics: CEN standards: Maintenance: Maintenance: Description: PPE: Characteristics: CEN standards: Maintenance: Maintenance: Maintenance: Description: PPE: Characteristics: CEN standards: Maintenance: Maintenance: Description: PPE: Characteristics: CEN standards: Maintenance: Mork footwear. CEN standards: CEN standards: Maintenance: Mork footwear. CEN standards:	Material:	PVC (polyvinyl chloride) Breakthrough time 480 Material thickness 0.35			
CEN standards:	Eye protection:				
CEN standards: EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Skin protection: PPE: Characteristics: CEN standards: EN 340 Maintenance: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Characteristics: CEN standards: Maintenance: Work footwear. Characteristics: CEN standards: Maintenance: Work footwear. Work footwear. This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear against any work against	PPE:	Face shield.			
Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Observations: Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Skin protection: PPE: Characteristics: CEN standards: In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: CEN standards: Maintenance: Maintenance: Work footwear. CES marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any of the professional use includes protection elements aimed at protecting users against any of the professional use includes protection elements aimed at protecting users against any of the professional use includes protection elements aimed at protecting users against any of the professional use includes protection elements aimed at protecting users against any of the professional use includes protection elements aimed at protecting users against any of the professional users against any of the	Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.			
Maintenance: Deservations: Deservations: Deservations: Deservations: Deservations: PPE: Characteristics: CEN standards: Maintenance: Deservations: Deservations: Deservations: Maintenance: Deservations: Deservations: PPE: Characteristics: CEN standards: Maintenance: Deservations: Deser	CEN standards:	EN 165, EN 166, EN 167, EN 168			
Skin protection: PPE: Protective clothing. Characteristics: CEN standards: EN 340 Maintenance: The protective clothing should offer a level of activity and the expected time of use. PPE: Work footwear for profections provided should not be a for hygienic reasons, it should not be used by other people. Work footwear for profescional use includes protection elements aimed at protecting users against any		Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should			
Observations: Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Skin protection: PPE: Characteristics: CEN standards: Maintenance: Description: PPE: Characteristics: CEN standards: Maintenance: Description: PPE: Characteristics: CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: CEN marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Maintenance:				
Skin protection: PPE: Protective clothing. Characteristics: CEN standards: EN 340 Maintenance: The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.		,			
PPE: Protective clothing. Characteristics: CEN standards: EN 340 Maintenance: The protective clothing should offer a level of comfort in line with the level of protection provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Observations:				
Characteristics: CEN standards: Maintenance: Observations: CEN standards: CEN standards: Maintenance: Maintenance: Observations: CEN standards: CEN standards: Maintenance: Observations: CEN standards: Maintenance: Observations: CEN standards: Maintenance: Observations: CEN standards: CEN standards: CEN standards: CEN standards: CEN standards: Maintenance: CEN standards: Maintenance: CEN standards: Maintenance: CEN standards: Maintenance: CEN standards: CEN standards: Maintenance: CEN standards: Maintenance: CEN standards: CEN stand					
CEN standards: Maintenance: Observations: CEN standards: Observations: CEN standards: Maintenance: Observations: CEN standards: Observations: Obse	PPE:				
CEN standards: Maintenance: Maintenance: Maintenance: Deservations: CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Characteristics: CEN standards: Maintenance: Maintenance: Maintenance: Work footwear. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Characteristics:				
the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Characteristics: CEN standards: CEN standards: Maintenance: Maintenance: Work footwear. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	CEN standards:				
The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.	Maintenance:				
Observations: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any					
of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	Observations				
PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	ODSCI VALIONS.	, , ,			
Characteristics: «CE» marking, category II. EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footbears for professional use includes protection elements aimed at protecting users against any	PPF:				
CEN standards: Maintenance: EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	—				
Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people. Work footware for professional use includes protection elements aimed at protecting users against any					
not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any	Maintenance				
Work footwear for professional use includes protection elements aimed at protecting users against any	maintenance:	not be used by other people.			
injury resulting from an accident	Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident			

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance:Liquid with characteristic odour

Colour: N.A./N.A.
Odour:N.A./N.A.
Odour threshold:N.A./N.A.
pH:N.A./N.A.
Melting point:>N.A./N.A.

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



Version: 11 Page 5 of 8
Revision date: 17/02/2017 Print date: 17/02/2017

Boiling Point:> 100 °C Flash point:> 100 °C Evaporation rate: N.A./N.A.

Inflammability (solid, gas): Non inflammable

Lower Explosive Limit: No aplicable Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:Bigger than the air Relative density:1.850 g/cm³ Solubility:N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: Miscible

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

2-butoxyethanol and its acetate are easily absorbed by the skin and can cause noxious effects to the kidneys.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 73.333 mg/kg

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 6 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

ATE (Oral) = 33.333 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
	Name	Log Pow	BCF	NOECs	Level
2-butoxyethanol,		0.0			Voncloss
N. CAS: 111-76-2	EC No: 203-905-0	0,8	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 7 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6. **14.1 UN number.**

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous. ICAO: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): Interior/exterior trim varnishes and woodstains, including opaque woodstains, water-borne

Phase I* (from 01/01/2007): 150 g/l Phase II* (from 01/01/2010): 130 g/l

(*) g/l ready to use

VOC content (p/p): 1,653 % VOC content: 30,571 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

(in accordance with Regulation (EU) 2015/830)

920014600000-HIDRON SP-146 White



 Version: 11
 Page 8 of 8

 Revision date: 17/02/2017
 Print date: 17/02/2017

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

Classification codes:

Acute Tox. 4 [Dermal] : Acute toxicity (Dermal), Category 4 Acute Tox. 4 [Inhalation] : Acute toxicity (Inhalation), Category 4

Acute Tox. 4 [Oral]: Acute toxicity (Oral), Category 4

Eye Irrit. 2 : Eye irritation, Category 2 Skin Irrit. 2 : Skin irritant, Category 2

It is recommended that the product only be employed for the purposes advised.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
111-76-2	2-butoxyethanol,	Registered

Abbreviations and acronyms used: BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration. PPE: Personal protection equipment. LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water. NOEC: No observed effect concentration.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.