

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.11.2019

Revision · 13 11 2019

SECTION 1: Identification of the substance/mixture and substance/mixture and of the substance/mixture and	he company/undertaking
For professional use only	
· 1.1 Product identifier For professional use only	
· Trade name: Thinner 2622	
 Article number: 2622 1.2 Relevant identified uses of the substance or mixture and uses advised of Application of the substance / the mixture Surface Coating Surface Coating Thinner Uses advised against Product is not intended, labelled or packaged for const 	
• 1.3 Details of the supplier of the safety data sheet	
• Supplier: HMG PAINTS LIMITED RIVERSIDE WORKS, COLLYHURST ROAD, MANCHESTER. M40 7RU UNITED KINGDOM TEL: +44 (0)161 205 7631 EMAIL: sales@hmgpaint.com	
• Further information obtainable from: sales@hmgpaint.com • 1.4 Emergency telephone number: +44 (0)161 205 7631 (Business hours)	
SECTION 2: Hazards identification	
SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture	
SECTION 2: Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008	
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 3 H226 Flammable liquid and vapour.	
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 3 H226 Flam. Liq. 3 H226 Flam. Liq. 3 H335-H336 May cause respiratory irritation. May cause	
SECTION 2: Hazards identification• 2.1 Classification of the substance or mixture• Classification according to Regulation (EC) No 1272/2008Flam. Liq. 3H226Flam. Liq. 3H226Flam. Dig. 3H335-H336May cause respiratory irritation. May causeAsp. Tox. 1H304May be fatal if swallowed and enters airway	tys.
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 3 H226 Flam. Liq. 3 H226 Flam. Liq. 3 H335-H336 May cause respiratory irritation. May cause Asp. Tox. 1 H304 May be fatal if swallowed and enters airway Aquatic Chronic 2 H411	tys.
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 3 H226 Flam. Liq. 3 H226 Flam. Liq. 3 H335-H336 May cause respiratory irritation. May cause Asp. Tox. 1 H304	tys.
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 3 H226 Flam. Liq. 3 H226 Flam. Liq. 3 H335-H336 May cause respiratory irritation. May cause Asp. Tox. 1 H304 May be fatal if swallowed and enters airwat Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effect • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.	tys.
SECTION 2: Hazards identification • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 3 H226 Flam. Liq. 3 H226 Flam. Liq. 3 H335-H336 May cause respiratory irritation. May cause Asp. Tox. 1 H304 H304 May be fatal if swallowed and enters airwat Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effect • 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. • Hazard pictograms	tys.

Printing date 13.11.2019

Revision: 13.11.2019

Trade name: Thinner 2622

	(Contd. of page 1)
· Precautionary st	tatements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P3	53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· 2.3 Other hazard	ds

· Results of PBT and vPvB assessment

· *PBT:* Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 918-668-5	Solvent naphtha (petroleum), light aromatic	>50- <i>≤</i> 100%
Reg.nr.: 01-2119455851-35-xxxx	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ↑ STOT SE 3, H335-H336	
	Chronic 2, H411; 🚯 STOT SE 3, H335-H336	
CAS: 67-63-0	propan-2-ol	>2.5-≤10%
EINECS: 200-661-7	🛞 Flam. Liq. 2, H225; 🚯 Eye Irrit. 2, H319; STOT SE 3,	
Reg.nr.: 01-2119457558-25-XXXX	<i>Н</i> 336	
Additional information: For the wording of the listed hazard phrases refer to section 16		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

 \cdot General information: Immediately remove any clothing soiled by the product.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Immediately rinse with water.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus

(Contd. on page 3)

Printing date 13.11.2019

Revision: 13.11.2019

Trade name: Thinner 2622

(Contd. of page 2)

SECTION 6: Accidental release measures	
\cdot 6.1 Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· 6.2 Environmental precautions:	
Do not allow product to reach sewage system or any water course.	
Prevent seepage into sewage system, workpits and cellars.	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
· 6.3 Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· 6.4 Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
SECTION 7: Handling and storage	
• 7.1 Precautions for safe handling	
Keep receptacles tightly sealed.	
Ensure good ventilation/extraction at the workplace.	
Prevent formation of aerosols.	
• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.	
Protect against electrostatic charges.	
i roteci agamai electrostatic charges.	

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

Solvent naphtha (petroleum), light aromatic

OEL Long-term value: 100 mg/m³

67-63-0 propan-2-ol

- WEL Short-term value: 1250 mg/m³, 500 ppm
 - Long-term value: 999 mg/m³, 400 ppm

· DNELs

Solvent naphtha (petroleum), light aromatic

Oral	DNEL	11 mg/day (Con)
Dermal		11 mg/day (Con)
		25 mg/day (Ind)
Inhalative	DNEL	32 mg/m ³ (Con)

(Contd. on page 4)

GB

Printing date 13.11.2019

Revision: 13.11.2019

Trade name: Thinner 2622

	(Contd. of page 3
	150 mg/m ³ (Ind)
ropan-2	-ol
DNEL	26 mg/day (Con)
	319 mg/day (Con)
	888 mg/day (Ind)
	89 mg/m ³ (Con)
	500 mg/m ³ (Ind)
	DNEL DNEL

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- *Respiratory protection:* When spraying the product, use a respiratory protective device.
- Protection of hands:

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 \cdot Eye protection:



Tightly sealed goggles

SECTION 9: Physical and ch	emical properties	
 9.1 Information on basic physical a General Information Appearance: 	nd chemical properties	
Form:	Liquid	
Colour:	Clear	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
• Change in condition Melting point/freezing point: Initial boiling point and boiling ra	-50 °C nge: 140 °C	
· Flash point:	>35 °C	
· Flammability (solid, gas):	Not applicable.	
		(Contd. on page 5)

Printing date 13.11.2019

Revision: 13.11.2019

Trade name: Thinner 2622

	(Contd. of page 4
· Ignition temperature:	>400 °C
· Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air, vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	5 hPa
Density at 20 °C:	0.867 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water at 20 °C:	0.05 g/l
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	$0.7 \ mm^{2}/s$
· Solvent content:	
Organic solvents:	100.0 %
Solids content:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
Solvent no	aphtha (pet	roleum), light aromatic
Oral	LD50	3,492 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (Rab)
Inhalative	LC50/4 h	6,193 mg/l (rat)
67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (Rat)
Dermal	LD50	13,900 mg/kg (Rab)
		(Contd. on page 6

Printing date 13.11.2019

Revision: 13.11.2019

(Contd. of page 5)

Trade name: Thinner 2622

Inhalative LC50/4 h >25 mg/l (Rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: Acute Fish toxicity Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %) LC50 9.22 mg/l Species: Oncorhynchus mykiss (rainbow trout) Exposure duration: 96 h

Acute toxicity for daphnia Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %) EC50 6.14 mg/l Species: Daphnia magna (Water flea) Exposure duration: 48 h

Acute toxicity for algae Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %) ErC50 2.9 mg/l Species: Pseudokirchneriella subcapitata (green algae) Exposure duration: 72 h

Acute bacterial toxicity Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %) EC50 1 - 10 mg/l

Ecotoxicology Assessment

Solvent naphtha (petroleum), light arom. (content of benzene less than 0,1 %) Chronic aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Data based on the safety data sheet (SDS) by the supplier.

 \cdot 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- **Remark:** Toxic for fish
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

(Contd. on page 7)

GE

Printing date 13.11.2019

Revision: 13.11.2019

(Contd. of page 6)

Trade name: Thinner 2622

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR	1263 PAINT RELATED MATERIAL ENVIRONMENTALLY HAZARDOUS
IMDG	PAINT RELATED MATERIAL (Solvent naphth (petroleum), light aromatic), MARINE POLLUTANT
IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.
Label	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances Solvent naphtha (petroleum), light aromatic
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30 E E S E
EMS Number: Stowage Category	<i>F-E,<u>S-E</u> A</i>
14.7 Transport in bulk according to Ann	
$\pi \pi $	Not applicable.

Printing date 13.11.2019

Revision: 13.11.2019


Trade name: Thinner 2622

	(Contd. of page 7)
· Transport/Additional information:	
· ADR	
\cdot Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
• Tunnel restriction code	D/E
· IMDG	
\cdot Limited quantities (LQ)	5L
\cdot Excepted quantities (\widetilde{EQ})	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III,
-	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

• Technical instructions (air):



- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Full text of H-Statements referred to under sections 2 and 3:
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department: LABORATORY
- · Contact: Health & Safety Officer
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

GB

Printing date 13.11.2019

Revision: 13.11.2019

Trade name: Thinner 2622

(Contd. of page 8)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
GB