

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** For professional use only
- **Trade name:** 2K Multi Surface Gloss Colours
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture** Surface Coating
- **Uses advised against** Product is not intended, labelled or packaged for consumer use.
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
HMG PAINTS LIMITED
RIVERSIDE WORKS, COLLYHURST ROAD,
MANCHESTER. M40 7RU
UNITED KINGDOM
TEL: +44 (0)161 205 7631
EMAIL: sales@hmgpaint.com
- **Further information obtainable from:** sales@hmgpaint.com
- **1.4 Emergency telephone number:** +44 (0)161 205 7631 (Business hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Xylene (mix)
- **Hazard statements**
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 1)

- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Xylene (mix) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	Butyl ethanoate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	2.5-10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.
Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately and show safety datasheet or label.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/extraction at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed and in a well-ventilated place.
Keep away from heat.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 3)

· 8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:****1330-20-7 Xylene (mix)**

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

123-86-4 Butyl ethanoate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

· DNELs**1330-20-7 Xylene (mix)**

Dermal	DNEL	108 mg/day (Con) 180 mg/day (Ind)
Inhalative	DNEL	14.8 mg/m ³ (Con) 77 mg/m ³ (Ind)

123-86-4 Butyl ethanoate

Oral	DNEL	2 mg/day (Con)
Dermal	DNEL	6 mg/day (Con) 11 mg/day (Ind)
Inhalative	DNEL	35.7 mg/m ³ (Con) 300 mg/m ³ (Ind)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL	1.67 mg/day (Con)
Dermal	DNEL	54.8 mg/day (Con) 153.5 mg/day (Ind)
Inhalative	DNEL	33 mg/m ³ (Con) 275 mg/m ³ (Ind)

· PNECs

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

CAS No. 123-86-4 Butyl Acetate

- Freshwater: 0.18 mg/l
- Marine water: 0.018 mg/l
- Fresh water sediment: 0.981 mg/kg
- Marine sediment: 0.0981 mg/kg
- Soil: 0.0903 mg/kg
- STP (sewage-treatment plant): 35.6 mg/l
- Intermittent use/release: 0.36 mg/l

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 4)

· Ingredients with biological limit values:**1330-20-7 Xylene (mix)**

BMGV 650 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection: When spraying the product, use a respiratory protective device.**· Protection of hands:**

Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:****Form:**

Liquid

Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition**Melting point/freezing point:**

Undetermined.

Initial boiling point and boiling range: 124 °C**· Flash point:**

26 °C

· Flammability (solid, gas):

Not applicable.

· Ignition temperature:

370 °C

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.093 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	NOT MISCIBLE
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	700 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	38.9 %
Solids content:	59.7 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products when stored and handled correctly

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene (mix)

Oral	LD50	5,000 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	11 mg/l (Rat)

123-86-4 Butyl ethanoate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	14,112 mg/kg (Rab)
Inhalative	LC50/4 h	23.4 mg/l (Rat)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 6)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (Rat)
Inhalative	LC50/4 h	>10.8 mg/l (Rat)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
 - Acute Fish toxicity
 - n*-Butyl acetate
 - LC50 18 mg/l
 - Species: *Pimephales promelas* (fathead minnow)
 - Exposure duration: 96 h
 - Chronic Fish toxicity
 - n*-Butyl acetate
 - No data available.
 - Acute toxicity for daphnia
 - n*-Butyl acetate
 - EC50 44 mg/l
 - Species: *Daphnia* (water flea)
 - Exposure duration: 48 h
 - Chronic toxicity to daphnia
 - n*-Butyl acetate
 - NOEC 23 mg/l
 - Species: *Daphnia magna* (Water flea)
 - Exposure duration: 21 d
 - Method: OECD Test Guideline 211
 - Acute toxicity for algae
 - n*-Butyl acetate
 - EC50 675 mg/l
 - Species: *Scenedesmus quadricauda* (Green algae)
 - Exposure duration: 72 h
 - Acute bacterial toxicity

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 7)

EC50 356 mg/l

Species: activated sludge

Exposure duration: 40 h

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**· **ADR**

1263 PAINT

· **IMDG, IATA**

PAINT

· **14.3 Transport hazard class(es)**· **ADR, IMDG, IATA**· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):**

30

· **Stowage Category**

A

· **14.7 Transport in bulk according to Annex II of****Marpol and the IBC Code**

Not applicable.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 8)

· Transport/Additional information:**· ADR****· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG**· Limited quantities (LQ)**

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information**· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**· National regulations:****· Technical instructions (air):**

Class	Share in %
NK	38.9

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.**· 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Full text of H-Statements referred to under sections 2 and 3:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Product safety department: LABORATORY**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 14.11.2019

Revision: 14.11.2019

Trade name: 2K Multi Surface Gloss Colours

(Contd. of page 9)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

GB