

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 1 of 14  
Print date: 09/09/2019

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: IRUFIRE TOP COAT IT-1 SEMI MATT  
Product Code: 390005903000

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Coating material for different surfaces

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **Industrias Químicas Irurena, S.A.**  
Address: Ctra. de Tolosa, s/nº. Apdo. 30  
City: 20730 Azpeitia  
Province: Gipuzkoa  
Telephone: 943 15 70 99  
Fax: 943 81 09 11  
E-mail: irurena@irurenagroup.com  
Web: <http://www.irurenagroup.com>

**1.4 Emergency telephone number:** 915 620 420 (Inst.Toxicologia) (Available 24 hours)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Irrit. 2 : Causes serious eye irritation.  
Flam. Liq. 2 : Highly flammable liquid and vapour.  
STOT SE 3 : May cause drowsiness or dizziness.  
Skin Irrit. 2 : Causes skin irritation.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

H statements:

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

P statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 2 of 14  
Print date: 09/09/2019

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378	In case of fire: Use extinguisher powder or CO2 to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains:  
butanone  
ethyl acetate  
n-butyl acetate

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene (Mixture of isomers)	10 - 50 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] butanone	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] ethyl acetate	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

## SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 3 of 14  
Print date: 09/09/2019

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

## SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Suitable extinguishing media:**

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 4 of 14  
Print date: 09/09/2019

### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.  
For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

### 7.3 Specific end use(s).

To be used within industrial facilities only

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 5 of 14  
Print date: 09/09/2019

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
xylene (Mixture of isomers)	1330-20-7	European Union [1]	<b>Eight hours</b>	50 (skin)	221 (skin)
			<b>Short term</b>	100 (skin)	442 (skin)
		United Kingdom [2]	<b>Eight hours</b>	50	220
			<b>Short term</b>	100	441
		United States [3] (Cal/OSHA)	<b>Eight hours</b>	100	
			<b>Short term</b>	150 (Ceiling) 300	
		United States [4] (NIOSH)	<b>Eight hours</b>	100	
			<b>Short term</b>	150	
		United States [5] (OSHA)	<b>Eight hours</b>	100	435
			<b>Short term</b>		
butanone	78-93-3	European Union [1]	<b>Eight hours</b>	200	600
			<b>Short term</b>	300	900
		United Kingdom [2]	<b>Eight hours</b>	200	600
			<b>Short term</b>	300	899
		United States [3] (Cal/OSHA)	<b>Eight hours</b>	200	
			<b>Short term</b>	300	
		United States [4] (NIOSH)	<b>Eight hours</b>	200	
			<b>Short term</b>	300	
		United States [5] (OSHA)	<b>Eight hours</b>	200	590
			<b>Short term</b>		
ethyl acetate	141-78-6	European Union [1]	<b>Eight hours</b>	200	734
			<b>Short term</b>	400	1468
		United Kingdom [2]	<b>Eight hours</b>	200	
			<b>Short term</b>	400	
		United States [3] (Cal/OSHA)	<b>Eight hours</b>	400	
			<b>Short term</b>		
		United States [4] (NIOSH)	<b>Eight hours</b>	400	
			<b>Short term</b>		
		United States [5] (OSHA)	<b>Eight hours</b>	400	1400
			<b>Short term</b>		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[5] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m <sup>3</sup> )
butanone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104

Revision date: 03/09/2019

Page 6 of 14

Print date: 09/09/2019

ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m <sup>3</sup> )
	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	734 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	367 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	1468 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	63 (mg/kg bw/day)
DNEL (General population)	Dermal, Long-term, Systemic effects	37 (mg/kg bw/day)	

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DNEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
butanone CAS No: 78-93-3 EC No: 201-159-2	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
	oral (Hazard for predators)	1000 (mg/kg food)
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	STP	650 (mg/L)
oral (Hazard for predators)	0,2 (g/kg food)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Coating material for different surfaces
Breathing protection:	

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)








IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 7 of 14  
Print date: 09/09/2019

PPE:	Filter mask for protection against gases and particles.				
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.				
CEN standards:	EN 136, EN 140, EN 405				
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Observations:	Filter Type needed: A2				
<b>Hand protection:</b>					
PPE:	Protective gloves.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
<b>Eye protection:</b>					
PPE:	Face shield.				
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.				
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.				
<b>Skin protection:</b>					
PPE:	Anti-static protective clothing.				
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.				
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.				
PPE:	Anti-static safety footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346				
Maintenance:	The footwear should be checked regularly				
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.				

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour  
Colour: See Technical Data Sheet  
Odour: With solvent  
Odour threshold: N.A./N.A.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

**Version: 104**  
**Revision date: 03/09/2019**

**Page 8 of 14**  
**Print date: 09/09/2019**

pH: N.A./N.A.  
Melting point: < 0 °C  
Boiling Point: 60 °C  
Flash point: 6 °C  
Evaporation rate: N.A./N.A.  
Inflammability (solid, gas): N.A./N.A.  
Lower Explosive Limit: 0,8% Aprox.  
Upper Explosive Limit: N.A./N.A.  
Vapour pressure: N.A./N.A.  
Vapour density: Bigger than the air  
Relative density: .920  
Solubility: In solvents  
Liposolubility: Miscible  
Hydrosolubility: Partially miscible  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: > 200 °C  
Decomposition temperature: > 200 (Catalyst 60 °C)°C  
Viscosity: See Technical Data Sheet  
Explosive properties: Not Explosive, but may form explosive mixtures with air  
Oxidizing properties: Non-Oxidizing (Except Catalyst)

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Dropping point: N.A./N.A.  
Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 9 of 14  
Print date: 09/09/2019

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;  
Not conclusive data for classification.

Acute Toxicity Estimate (ATE):  
Mixtures:  
ATE (Dermal) = 4.121 mg/kg

b) skin corrosion/irritation;  
Product classified:  
Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;  
Product classified:  
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;  
Not conclusive data for classification.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Not conclusive data for classification.

h) STOT-single exposure;  
Product classified:  
Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Not conclusive data for classification.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 10 of 14  
Print date: 09/09/2019

### Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
butanone CAS No: 78-93-3                      EC No: 201-159-0	0,29	-	-	Very low
ethyl acetate CAS No: 141-78-6                      EC No: 205-500-4	0,73	-	-	Very low

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13 DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.  
Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 11 of 14  
Print date: 09/09/2019

### 14.1 UN number.

UN No: UN1263

### 14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT, 3, PG II, (D/E)

IMDG: UN 1263, PAINT, 3, PG II

ICAO/IATA: UN 1263, PAINT, 3, PG II

### 14.3 Transport hazard class(es).

Class(es): 3

### 14.4 Packing group.

Packing group: II

### 14.5 Environmental hazards.

Marine pollutant: No

### 14.6 Special precautions for user.

F-E,S-E Labels: 3



Hazard number: 33

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills):

Proceed in accordance with point 6.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

#### Volatile organic compound (VOC)

VOC content (p/p): 75,176 %

VOC content: 691,615 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
----------------------------------------------------------------------------	---------------------------

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

IRURENA GROUP

Version: 104  
Revision date: 03/09/2019

Page 12 of 14  
Print date: 09/09/2019

### 20. Organostannic compounds

1. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture is acting as biocide in free association paint.
2. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture acts as biocide to prevent the fouling by micro-organisms, plants or animals of:
  - (a) all craft irrespective of their length intended for use in marine, coastal, estuarine and inland waterways and lakes;
  - (b) cages, floats, nets and any other appliances or equipment used for fish or shellfish farming;
  - (c) any totally or partly submerged appliance or equipment.
3. Shall not be placed on the market, or used, as substances or in mixtures where the substance or mixture is intended for use in the treatment of industrial waters.
4. Tri-substituted organostannic compounds:
  - (a) Tri-substituted organostannic compounds such as tributyltin (TBT) compounds and triphenyltin (TPT) compounds shall not be used after 1 July 2010 in articles where the concentration in the article, or part thereof, is greater than the equivalent of 0,1 % by weight of tin.
  - (b) Articles not complying with point (a) shall not be placed on the market after 1 July 2010, except for articles that were already in use in the Community before that date.
5. Dibutyltin (DBT) compounds:
  - (a) Dibutyltin (DBT) compounds shall not be used after 1 January 2012 in mixtures and articles for supply to the general public where the concentration in the mixture or the article, or part thereof, is greater than the equivalent of 0,1 % by weight of tin.
  - (b) Articles and mixtures not complying with point (a) shall not be placed on the market after 1 January 2012, except for articles that were already in use in the Community before that date.
  - (c) By way of derogation, points (a) and (b) shall not apply until 1 January 2015 to the following articles and mixtures for supply to the general public:
    - one-component and two-component room temperature vulcanisation sealants (RTV-1 and RTV-2 sealants) and adhesives,
    - paints and coatings containing DBT compounds as catalysts when applied on articles,
    - soft polyvinyl chloride (PVC) profiles whether by themselves or coextruded with hard PVC,
    - fabrics coated with PVC containing DBT compounds as stabilisers when intended for outdoor applications,
    - outdoor rainwater pipes, gutters and fittings, as well as covering material for roofing and façades,
  - (d) By way of derogation, points (a) and (b) shall not apply to materials and articles regulated under Regulation (EC) No 1935/2004.
6. Dioctyltin (DOT) compound:
  - (a) Dioctyltin (DOT) compounds shall not be used after 1 January 2012 in the following articles for supply to, or use by, the general public, where the concentration in the article, or part thereof, is greater than the equivalent of 0,1 % by weight of tin:
    - textile articles intended to come into contact with the skin,
    - gloves,
    - footwear or part of footwear intended to come into contact with the skin,
    - wall and floor coverings,
    - childcare articles,
    - female hygiene products,
    - nappies,
    - two-component room temperature vulcanisation moulding kits (RTV-2 moulding kits).
  - (b) Articles not complying with point (a) shall not be placed on the market after 1 January 2012, except for articles that were already in use in the Community before that date.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



IRURENA GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

Version: 104  
Revision date: 03/09/2019

Page 13 of 14  
Print date: 09/09/2019

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4  
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4  
Eye Irrit. 2 : Eye irritation, Category 2  
Flam. Liq. 2 : Flammable liquid, Category 2  
Flam. Liq. 3 : Flammable liquid, Category 3  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3  
Skin Irrit. 2 : Skin irritant, Category 2

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
1330-20-7	xylene (Mixture of isomers)	Registered
78-93-3	butanone	Registered
141-78-6	ethyl acetate	Registered

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



**IRURENA**GROUP

## 390005903000-IRUFIRE TOP COAT IT-1 SEMI MATT

**Version: 104**

**Revision date: 03/09/2019**

**Page 14 of 14**

**Print date: 09/09/2019**

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.