

WHITE SPIRIT

Page: 1

Compilation date: 07/12/2012

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WHITE SPIRIT

Product code: \$180

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Solvents With Safety Ltd

Units 1 - 4

Plumtree Farm Ind Est

Harworth
Doncaster
DN11 8EW
United Kingdom

Tel: 01302 711733

Fax: 01302 711744

Email: sales@solventswithsafety.co.uk

1.4. Emergency telephone number

Emergency tel: 08445605341

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; STOT SE 3:

H336; Aquatic Chronic 2: H411

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause

drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





WHITE SPIRIT

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331: Do NOT induce vomiting.

P403: Store in a well-ventilated place.

P235: Keep cool.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C13-C16,RICH, N-ALKANES,ISOALKANES,CYCLICS, <0.03% AROMATICS

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	-	Flam. Gas 1: H220; Carc. 1B: H350; Muta. 1B: H340; Press. Gas: H280	95.000%
XYLENE				
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	3.000%
MESITYLENE				
203-604-4	108-67-8	-	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1.000%
ETHYLBENZE	ENE			
202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1.000%

Contains: Mesitylene (1,2,3,-TRYMETHYLBENZENE)

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Drench the affected skin with running

water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

WHITE SPIRIT

Page: 3

Inhalation: If unconscious, check for breathing and apply artificial respiration if necessary. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be redness or whiteness of the skin in the area of exposure. An itchy rash

may occur at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and

vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. There may be

a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: There may be drowsiness, slurred speech, muscular weakness, muscle twitching,

tremor, blurred vision, dilated pupils and shock. There may be vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Vapour may travel considerable distance to source of ignition and flash back. Highly

flammable. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Do not attempt to take action

without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the

neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks. Mix with sand or vermiculite.

WHITE SPIRIT

Page: 4

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden. Use non-

sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Prevent the build up of electrostatic charge in the immediate area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-

MESITYLENE

1	UK	25 ppm	_	-	-	

ETHYLBENZENE

UK			
	441 mg/m3	552 mg/m3	
	441 ma/m3		

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure all engineering measures

mentioned in section 7 of SDS are in place.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus

must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles.

Skin protection: Solvent resistant protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

WHITE SPIRIT

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Kinematic viscosity: 0.95mm2/s

Flash point°C: >=38

Autoflammability°C: >230

Vapour pressure: <5hPa Relative density: 774-795

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

WHITE SPIRIT

Page: 6

MESITYLENE

IPR GPG LDLO	1303	mg/kg
--------------	------	-------

ETHYLBENZENE

IPR	MUS	LD50	2624	μl/kg
ORL	RAT	LD50	3500	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Germ cell mutagenicity		Hazardous: calculated
Carcinogenicity		Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be redness or whiteness of the skin in the area of exposure. An itchy rash

may occur at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and

vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. There may be

a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: There may be drowsiness, slurred speech, muscular weakness, muscle twitching,

tremor, blurred vision, dilated pupils and shock. There may be vomiting and diarrhoea.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Absorbed only slowly into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

WHITE SPIRIT

Page: 7

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Solvent reclamation/regeneration.

Waste code number: 08.03.12

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1300

14.2. UN proper shipping name

Shipping name: TURPENTINE SUBSTITUTE

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

WHITE SPIRIT

Page: 8

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.