



TECHNICAL DATA SHEET

M561

WATERBASED VENEER TREATMENT FOR FIRE RETARDENT SYSTEMS

PRODUCT DESCRIPTION

Fire retardant salt solution.

AREAS OF USE

For application to veneers to upgrade their fire retardant properties on fire retardant boards when using fire retardant finishing systems.

PRODUCT CHARACTERISTICS

Clear water based salt solution that does not alter the colour of timber or affect the clarity of finishing systems.

METHODS OF APPLICATION AND USE OF PRODUCT

Prior to finishing, spray or brush apply a liberal coat to the areas to be treated, allow soaking and penetrating briefly before removing the excess with a cloth.

MIXING PROCEDURE

Supplied ready to use.

DATA

Solid content	15%
Density kg/ltr @ 20°C	1.07
Number of coats	1
Drying time @ 20°C in well ventilated area	Touch dry 30 mins. Over coating after 2 hours

STORAGE

The product should not be stored at temperature below 10°C as the solution may begin to break down. If this occurs the product needs to be heated to 30°C and stirred to redissolve the salts.

FURTHER INFORMATION

Read the separate Health and Safety sheet prior to use.

This is just one of a wide range of industrial wood coatings from Sherwin Williams. Should you require any further information on this, or any other product within our range, simply contact us at the address below.

N.B.: Data provided on this Technical Data Sheet correspond to our best knowledge and experience. We assure consistency on the chemical-physical characteristics of our products, within the tolerance limits specified on our Technical Data Sheets. Responsibility of final result of product application is fully up to the users, who shall make sure that the product corresponds to their own needs with regard to application system, to substrates used as well as to working conditions.

WARNING: Actual viscosity of some pigmented and/or thixotropic products may differ from the viscosity shown on the Technical Data Sheet. Differences are to be regarded as acceptable if within 30% maximum.