



Patent Knotting

PRODUCT DATA

Description:

Traditionally shellac based sealer for resinous knots on timber.

Area of use:

Interior and exterior

Substrates:

Wood

Packing:

5 Litre

Physical Constants:

Colour:	Dark Amber
Finish:	Gloss
Volume solids:	33%
Theoretical spreading rate:	16 sq.meters per litre
Flash point:	18°C
Specific gravity:	0.88
Dry to touch:	15 – 20 minutes
Overcoating time:	30 minutes

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush Cloth
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

*Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.*

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.