



TEXTURED FINISHES AND EXTERIOR EMULSIONS

A highly flexible coating, suitable for wood, plaster and brick, Sayerlack textured finishes and exterior emulsions can be used both internally and externally, with a guaranteed 10 years durability and an expected 40 year service life. The finishes are highly resistant to mould and algae growth and are ideal for bridging hairline cracks and minor surface irregularities. Application by roller, trowel, brush or spray, in a wide range of colours and textures, the product is complemented by a wide range of exterior and interior wood finishes and special effect products from the Sayerlack furniture coatings and industrial joinery ranges.

F1659 TEXTURE FINISHES

- Will give guaranteed 10 years durability and an expected 40 year service life, when used according to the specification.
- Highly resistant to mould and algae surface growths.
- Can be worked while wet to give a wide range of decorative textures.
- Ideal for bridging hairline cracks and minor surface irregularities.

- Available in a range of 10 standard colours. Other colours available on request.
- Highly resistant to cracking at uPVC window and door joints.
- Can be overcoated with F2212 exterior emulsions.
- Upgrades timber substrate to Class 2 Surface Spread of Flame (BS476 part 7).
- Maintains Class 1 Surface Spread of Flame on Class 1 board (BS476 part 7).



F1659 TEXTURE FINISHES

APPLICATION	BRUSH, ROLLER, TROWEL AND TEXTURE SPRAY EQUIPMENT
COVERAGE	1.5 M ² TO 2.0 M ² PER LITRE
RECOMMENDED APPLICATION THICKNESS	500 — 750 MICRONS WET FILM THICKNESS
DRYING TIME	SURFACE DRY: 4-8 HOURS. THOROUGH DRY: 2 DAYS
MAINTENANCE	OVERCOAT EVERY 2-3 YEARS WITH SAYERLACK F2212 EXTERIOR EMULSION
CAN SIZES	10 LITRE BUCKETS

F1659 Texture Finishes are suitable for use on primed external surfaces as used in park home construction, but can also be applied to plaster and brick providing all surfaces are clean and free from flaking or loose material. The product is ready to use.

F2212 EXTERIOR EMULSIONS

- Highly resistant to mould and algae surface growths.
- Designed to enhance or change the colour of Sayerlack textured finishes.
- Manufactured from the same acrylic formula as Sayerlack textured finishes.

F3404 Primer sealer

F1660 Super smooth texture F2587 Cauking/Scrim tape adhesive and Filling compound

- Available in 10 standard colours.
- Other colours available on request.



F2212 EXTERIOR EMULSION

ADDITIONAL PRODUCTS

F2854 Stain block primer

APPLICATION	BRUSH, ROLLER AND CONVENTIONAL SPRAY EQUIPMENT
COVERAGE	4 M ² TO 5 M ² PER LITRE
DRYING TIME	SURFACE DRY: 1-2 HOURS. THOROUGH DRY: 4 HOURS
CAN SIZES	10 LITRE BUCKETS

PLEASE NOTE

PROTECT FROM FROST and do not apply at temperatures below 5°C. All Sayerlack textured finishes and exterior emulsions are waterbased and cleaning should be undertaken with tap water.

F2212 Exterior Emulsions are designed for use on exterior textured surfaces, but is also ideal for timber, plaster, concrete and brick surface. The product is ready to use.

Further advice on the use of Sayerlack textured finishes or any information on the other products supplied by Sherwin-Williams UK Coatings Ltd is available on request from the address opposite.



LINEA BLU is a range of acrylic, professional quality exterior coatings for wood in either a wood stain or an opaque finish.

06/2006

Z02A12UK

Sayerlack S.r.I. assumes no contractual liability or responsibility in regards to the texts and photographs included herein.





A1 Business Park - Knottingley - West Yorkshire - WF11 OBU - England tel +44 (D) 1977 673363 - fax +44 (D) 1977 673521 - info@sayerlack.co.uk - www.sayerlack.co.uk **Technical Service:** tel +39 051 770770 - fax +39 051 770521 - customerservice@sayerlack.co